

UK Declaration of Conformity

Nr : JYT5354200-01

Products identification :

Type of products : Electronic pressure sensors

Trademark : **Telemecanique Sensors**

Models : **XMLR...**
(complete list of models covered in page 2)

We, **TMSS France (Manufacturer)** and **Yageo TMSS UK Limited (UK Representative)**, declare under our sole responsibility that the products to which this declaration refers comply with Essential Requirements of the following Regulation(s) :

Electromagnetic Compatibility Regulations : **SI 2016 No. 1091**

Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 : **SI 2012 No. 3032**

Product's conformity has been assessed by applying the following designated standard(s) :

BS EN 61326-1:2013

BS EN 61326-2-3:2013

BS EN IEC 63000:2018

When subject to installation, maintenance and use conforming to their intended purpose, to regulations and standards applicable in the country where they are installed, to the supplier's instructions and to accepted state of the art.



Tony KUMETA

General Manager, UK&I

Issued at : Harrogate – UNITED KINGDOM

Emission date : February 27th, 2024

Manufacturer :
TMSS France

Tour Egho – 2 avenue Gambetta
92400 Courbevoie – FRANCE

UK Representative :
Yageo TMSS UK Limited

2 North Park Road
Harrogate, HG1 5PA – UNITED KINGDOM

Technical Documentation authority :
TMSS France

Boulevard Salvador Allende – ZI n°3
16340 L'Isle d'Espagnac – FRANCE

Appendix

Nr : JYT5354200-01

List of product models covered by the present UK Declaration of Conformity

XMLR	010	G	1	P	2	5
I	II	III	IV	V	VI	VII

I	Product type	
	XMLR	: Electronic pressure sensor, with 4-digit display
II	Pressure range	
	...	: ... = 3 digits giving the pressure range (in bar)
	•D•	: •D• = 3 digits giving the pressure range, for low pressure sensing (up to •,• bar)
	M••	: M•• = 3 digits giving the pressure range, for depression sensing (up to –•• bar)
III	Pressure unit and type of cell	
	G	: Gauge bar, ceramic cell
	M	: Gauge bar, metallic cell
IV	Number of outputs	
	0	: No output (test input)
	1	: 1 discrete output
	2	: 2 discrete outputs
V	Discrete output type	
	T	: No output (test input)
	N	: NPN transistor
	P	: PNP transistor
VI	Analogue output type	
	0	: Without analogue output
	2	: 4...20 mA
	7	: 0...10 V
VII	Fluid connection type	
	5	: G 1/4 A DIN 3852-Y (female)
	6	: 1/4" - 18 NPT (female)

NOTE : These references may be followed by 1 to 3 alphanumeric digits, to denote assembly, marking or packaging variations, without impact on products characteristics and/or compliance.