

Date: 19/05/2025

Object: Telemecanique_Sensors_Products REACH declaration (REACH: Registration, Evaluation, Authorization and Restriction of Chemicals)

Dear Customer,

TMSS France and its affiliates have undertaken to strictly comply with the REACH regulation N° 1907/2006 for the declaration of Substances of Very High Concern (hereafter referred to as SVHC), authorization (Annex XIV) and restriction (Annex XVII).

As per our commitment under article 33 of the said regulation, you will find attached here below information, to the best of our knowledge and as of the date of publication of this information, regarding the presence of SVHC in Telemecanique Sensors' products.

This information may evolve over time based on the improved knowledge resulting from both additional information provided by our suppliers and our own investigations.

Best Regards,



Didier BARON
Head of Telemecanique Sensors PBU
YAGEO Group

TMSS France and its affiliates

Postal address / Adresse postale :
Tour Eqho 2 avenue Gambetta 92400 COURBEVOIE - France

Legal information / Mentions légales
Société par actions simplifiée au capital de 366 931 214 euros
908 125 255 RCS Nanterre – code APE : 2640Z
Siret : 90812525500012
n° ident. TVA : FR 21 908 125 255
Siège Social : Tour Eqho - 2 avenue Gambetta - 92400 COURBEVOIE – France

The data shown in this spreadsheet are related to the following version of the REACH regulation: June 2024 candidate list.

Commercial References	Description	SCIP ID
XUSL4E30H061N	SAFETY LC E T4 R30 H610 D4-12M	-
XUSL4E30H121N	SAFETY LC E T4 R30 H1210 D4-12M	-
XUSL4E30H091N	SAFETY LC E T4 R30 H910 D4-12M	-
XUSL4E30H181N	SAFETY LC E T4 R30 H1810 D4-12M	-
XUSL4E30H046N	SAFETY LC E T4 R30 H460 D4-12M	-
XUSL4E4BB091N	SAFETY LC E T4 4B H910 D4-12M	-
XUSL4E30H106N	SAFETY LC E T4 R30 H1060 D4-12M	-
XUSL4E30H151N	SAFETY LC E T4 R30 H1510 D4-12M	-
XUSL4E14F031N	SAFETY LC E T4 R14 H310 D3-6M	-
XUSL4E30H076N	SAFETY LC E T4 R30 H760 D4-12M	-
XUSL4E3BB081N	SAFETY LC E T4 3B H810 D4-12M	-
XUSL4E2BB051N	SAFETY LC E T4 2B H510 D4-12M	-
XUSL4E14F061N	SAFETY LC E T4 R14 H610 D3-6M	-
XUSL4E14F046N	SAFETY LC E T4 R14 H460 D3-6M	-
XUSL4E30H166N	SAFETY LC E T4 R30 H1660 D4-12M	-
XUSL2E30H061N	SAFETY LC E T2 R30 H610 D4-12M	-
XUSL2E4BB091N	SAFETY LC E T2 4B H910 D4-12M	-
XUSL4E2BB051L	SAFETY LC E T4 2B H510 D10-20M	-
XUSL4E30H031N	SAFETY LC E T4 R30 H310 D4-12M	-
XUSL4E14F091N	SAFETY LC E T4 R14 H910 D3-6M	-
XUSL2E30H046N	SAFETY LC E T2 R30 H460 D4-12M	-
XUSL2P30H046SSE	SAFETY LIGHT CURTAIN H=460MM	-
XUSL4E14F016N	SAFETY LC E T4 R14 H160 D3-6M	-
XUSL2E30H151N	SAFETY LC E T2 R30 H1510 D4-12M	-
XUSL2E30H121N	SAFETY LC E T2 R30 H1210 D4-12M	-
XUSL2E30H181N	SAFETY LC E T2 R30 H1810 D4-12M	-
XUSL2E30H026NDZ	XUSL type 2 Hand protection Std sensing range Hp 260 mm, R 30mm	-
XUSL2E30H091N	SAFETY LC E T2 R30 H910 D4-12M	-
XUSL4E30H136N	SAFETY LC E T4 R30 H1360 D4-12M	-
XUSL4E14F106N	SAFETY LC E T4 R14 H1060 D3-6M	-
XUSL4E14F076N	SAFETY LC E T4 R14 H760 D3-6M	-
XUSL4E30H076LWH	SAFETY LC E T4 R30 H760 D8-17M IP69H	-
XUSL2E30H106N	SAFETY LC E T2 R30 H1060 D4-12M	-
XUSL2E30H026N	SAFETY LC E T2 R30 H260 D4-12M	-
XUSL4E14F181N	SAFETY LC E T4 R14 H1810 D3-6M	-
XUSL2E30H076N	SAFETY LC E T2 R30 H760 D4-12M	-
XUSL2E3BB081N	SAFETY LC E T2 3B H810 D4-12M	-
XUSL4E30H016N	SAFETY LC E T4 R30 H160 D4-12M	-
XUSL4E3BB081L	SAFETY LC E T4 3B H810 D10-20M	-
XUSL4E30H151L	SAFETY LC E T4 R30 H1510 D10-20M	-
XUSL4E30H076NTQ	SAFETY LIGHT CURTAIN H=760MM E T4 R30 D4-12M BULK PACKAGING MOQ25	-
XUSL4E30H061L	SAFETY LC E T4 R30 H610 D10-20M	-
XUSL2E30H031N	SAFETY LC E T2 R30 H310 D4-12M	-
XUSL4E4BB091L	SAFETY LC E T4 4B H910 D10-20M	-
XUSL2E2BB051N	SAFETY LC E T2 2B H510 D4-12M	-
XUSL2E30H016N	SAFETY LC E T2 R30 H160 D4-12M	-
XUSL4E14F151N	SAFETY LC E T4 R14 H1510 D3-6M	-
XUSL4E30H106LWH	SAFETY LC E T4 R30 H1060 D8-17M IP69H	-
XUSL4E30H076L	SAFETY LC E T4 R30 H760 D10-20M	-
XUSL4E30H106L	SAFETY LC E T4 R30 H1060 D10-20M	-
XUSL4E30H136L	SAFETY LC E T4 R30 H1360 D10-20M	-
XUSL4E30H151NTQ	SAFETY LIGHT CURTAIN H=1510MM E T4 R30 D4-12M BULK PACKAGING MOQ25	-
XUSL4E30H106LWC	SAFETY LC E T4 R30 H1060 D8-17M IP69	-
XUSL4E30H181L	SAFETY LC E T4 R30 H1810 D10-20M	-
XUSL4E30H026N	SAFETY LC E T4 R30 H260 D4-12M	-
XUSL4E14F121N	SAFETY LC E T4 R14 H1210 D3-6M	-
XUSL2E30H136N	SAFETY LC E T2 R30 H1360 D4-12M	-
XUSL4E30H046L	SAFETY LC E T4 R30 H460 D10-20M	-
XUSL2E30H166N	SAFETY LC E T2 R30 H1660 D4-12M	-
XUSL4E14F166N	SAFETY LC E T4 R14 H1660 D3-6M	-
XUSL4E30H091LWH	SAFETY LC E T4 R30 H910 D8-17M IP69H	-
XUSL2P30H031SSE	SAFETY LIGHT CURTAIN H=310MM	-

TMSS France and its affiliates

Postal address / Adresse postale :
Tour Eqho 2 avenue Gambetta 92400 COURBEVOIE - France

Legal information / Mentions légales
Société par actions simplifiée au capital de 366 931 214 euros
908 125 255 RCS Nanterre – code APE : 2640Z
Siret : 90812525500012
n° ident. TVA : FR 21 908 125 255
Siège Social : Tour Eqho - 2 avenue Gambetta - 92400 COURBEVOIE – France

XUSL4E30H091L	SAFETY LC E T4 R30 H910 D10-20M	-
XUSL4E30H061S88	KIT: XUSL Sn 20m + access fixed 180	-
XUSL4E30H031L	SAFETY LC E T4 R30 H310 D10-20M	-
XUSL4E30H166L	SAFETY LC E T4 R30 H1660 D10-20M	-
XUSL4E30H121L	SAFETY LC E T4 R30 H1210 D10-20M	-
XUSL4MA4BB091N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 4B H=91CM D4- 12M	-
XUSL4MB40H181N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 R40 H=181CM D4- 12M	-
XUSL4E14F136N	SAFETY LC E T4 R14 H1360 D3-6M	-
XUSL4E3BB081LWC	SAFETY LC E T4 3B H810 D8-17M IP69	-
XUSL4MA30H091N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 R30 H=91CM D4-12M	-
XUSL4MA40H121N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 R40 H121CM D4-12M	-
XUSL4E30H076NS1	SAFETY LC E T4 R30 H760 D4-12M SLAVE1	-
XUSL2E30H061NWH	SAFETY LC E T2 R30 H610 D3-10M IP69H	-
XUSL4MA30H046N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 R30 H=46CM D4-12M	-
XUSL4MA3BB081N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 3B H=81CM D4- 12M	-
XUSL2E30H106NWC	SAFETY LC E T2 R30 H1060 D3-10M IP69	-
XUSL4E30H076NM	SAFETY LC E T4 R30 H760 D4-12M MASTER	-
XUSL4MA2BB051N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 2B H=51CM D4- 12M	-
XUSL4E30H016L	SAFETY LC E T4 R30 H160 D10-20M	-
XUSL4E4BB091LWH	SAFETY LC E T4 4B H910 D8-17M IP69H	-
XUSL4E30H106NM	SAFETY LC E T4 R30 H1060 D4-12M MASTER	-
XUSL4MA40H226N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 R40 H226CM D4-12M	-
XUSL4MA30H151N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 R30 H151CM D4-12M	-
XUSL4MB3BB081N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 3B H=81CM D4-12M	-
XUSL4E30H181LWC	SAFETY LC E T4 R30 H1810 D10-20M IP69	-
XUSL4MB2BB051N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 2B H=51CM D4-12M	-
XUSL4MB4BB091N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 4B H=091 D4-12M	-
XUSL4E14F046NM	SAFETY LC E T4 R14 H460 D3-6M MASTER	-
XUSL4E14F046NWH	SAFETY LC E T4 R14 H460 D2-5M IP69H	-
XUSL4E14F031NWH	SAFETY LC E T4 R14 H310 D2-5M IP69H	-
XUSL4E14F046NS2	SAFETY LC E T4 R14 H460 D3-6M SLAVE2	-
XUSL4E30H061LWH	SAFETY LC E T4 R30 H610 D8-17M IP69H	-
XUSL2E30H091NWC	SAFETY LC E T2 R30 H910 D3-10M IP69	-
XUSL4MA30H031N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 R30 H=31CM D4-12M	-
XUSL4MA30H061N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 R30 H=61CM D4-12M	-
XUSL4MB30H031N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 R30 H=31CM D4-12M	-
XUSL4E30H091LWC	SAFETY LC E T4 R30 H910 D8-17M IP69	-
XUSL4MA40H136N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 R40 H136CM D4-12M	-
XUSL4MB30H136N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 R30 H=136CM D4- 12M	-
XUSL4E14F076NS1	SAFETY LC E T4 R14 H760 D3-6M SLAVE1	-
XUSL4MA40H151N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 R40 H151CM D4-12M	-
XUSL4MB40H106N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 R40 H=106CM D4- 12M	-
XUSL4E14F046NS1	SAFETY LC E T4 R14 H460 D3-6M SLAVE1	-
XUSL4MB40H091N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 R40 H=91CM D4-12M	-
XUSL4E30H046LWH	SAFETY LC E T4 R30 H460 D8-17M IP69H	-
XUSL4E2BB051NS2	SAFETY LC E T4 2B H510 D4-12M SLAVE2	-

TMSS France and its affiliates

Postal address / Adresse postale :
Tour Eqho 2 avenue Gambetta 92400 COURBEVOIE - France

Legal information / Mentions légales
Société par actions simplifiée au capital de 366 931 214 euros
908 125 255 RCS Nanterre – code APE : 2640Z
Siret : 90812525500012
n° ident. TVA : FR 21 908 125 255
Siège Social : Tour Eqho - 2 avenue Gambetta - 92400 COURBEVOIE – France

XUSL4E14F031NM	SAFETY LC E T4 R14 H310 D3-6M MASTER	-
XUSL4E2BB051NS1	SAFETY LC E T4 2B H510 D4-12M SLAVE1	-
XUSL4E14F031NS1	SAFETY LC E T4 R14 H310 D3-6M SLAVE1	-
XUSL2E30H046NWC	SAFETY LC E T2 R30 H460 D3-10M IP69	-
XUSL4MB30H046N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 R30 H=46CM D4-12M	-
XUSL4E30H046NS1	SAFETY LC E T4 R30 H460 D4-12M SLAVE1	-
XUSL2E30H046NWH	SAFETY LC E T2 R30 H460 D3-10M IP69H	-
XUSL2E30H061NWC	SAFETY LC E T2 R30 H610 D3-10M IP69	-
XUSL2E30H076NWC	SAFETY LC E T2 R30 H760 D3-10M IP69	-
XUSL2E30H076NWH	SAFETY LC E T2 R30 H760 D3-10M IP69H	-
XUSL2E30H091NWH	SAFETY LC E T2 R30 H910 D3-10M IP69H	-
XUSL2E30H106NWH	SAFETY LC E T2 R30 H1060 D3-10M IP69H	-
XUSL2P30H046N	SAFETY LIGHT CURTAIN H=460MM P T2 R30 D4	-
XUSL4E14F016S88	KIT SAFETY LIGHT CURTAIN H=160MM	-
XUSL4E14F031NWC	SAFETY LC E T4 R14 H310 D2-5M IP69	-
XUSL4E14F046NWC	SAFETY LC E T4 R14 H460 D2-5M IP69	-
XUSL4E14F061NM	SAFETY LC E T4 R14 H610 D3-6M MASTER	-
XUSL4E14F061NS1	SAFETY LC E T4 R14 H610 D3-6M SLAVE1	-
XUSL4E14F061NS2	SAFETY LC E T4 R14 H610 D3-6M SLAVE2	-
XUSL4E14F061NWC	SAFETY LC E T4 R14 H610 D2-5M IP69	-
XUSL4E14F061NWH	SAFETY LC E T4 R14 H610 D2-5M IP69H	-
XUSL4E14F076NM	SAFETY LC E T4 R14 H760 D3-6M MASTER	-
XUSL4E14F076NS2	SAFETY LC E T4 R14 H760 D3-6M SLAVE2	-
XUSL4E14F076NWC	SAFETY LC E T4 R14 H760 D2-5M IP69	-
XUSL4E14F076NWH	SAFETY LC E T4 R14 H760 D2-5M IP69H	-
XUSL4E14F091NM	SAFETY LC E T4 R14 H910 D3 6M MASTER	-
XUSL4E14F121NM	SAFETY LIGHT CURTAIN H=1210MM E T4 R14 F NORMAL MASTER	-
XUSL4E14F181NM	SAFETY LIGHT CURTAIN H=1810MM E T4 R14 F NORMAL MASTER	-
XUSL4E2BB051LWC	SAFETY LC E T4 2B H510 D8-17M IP69	-
XUSL4E2BB051LWH	SAFETY LC E T4 2B H510 D8-17M IP69H	-
XUSL4E2BB051NM	SAFETY LC E T4 2B H510 D4-12M MASTER	-
XUSL4E30H046LWC	SAFETY LC E T4 R30 H460 D8-17M IP69	-
XUSL4E30H046NM	SAFETY LC E T4 R30 H460 D4-12M MASTER	-
XUSL4E30H046NS2	SAFETY LC E T4 R30 H460 D4-12M SLAVE2	-
XUSL4E30H061LWC	SAFETY LC E T4 R30 H610 D8-17M IP69	-
XUSL4E30H061NM	SAFETY LC E T4 R30 H610 D4-12M MASTER	-
XUSL4E30H061NS1	SAFETY LC E T4 R30 H610 D4-12M SLAVE1	-
XUSL4E30H061NS2	SAFETY LC E T4 R30 H610 D4-12M SLAVE2	-
XUSL4E30H076LWC	SAFETY LC E T4 R30 H760 D8-17M IP69	-
XUSL4E30H076NS2	SAFETY LC E T4 R30 H760 D4-12M SLAVE2	-
XUSL4E30H091NM	SAFETY LC E T4 R30 H910 D4-12M MASTER	-
XUSL4E30H091NS1	SAFETY LC E T4 R30 H910 D4-12M SLAVE1	-
XUSL4E30H091NS2	SAFETY LC E T4 R30 H910 D4-12M SLAVE2	-
XUSL4E30H091S88	KIT SAFETY LIGHT CURTAIN H=910MM E T4 R30 D4-12M AND BRACKET XUSZBSS4	-
XUSL4E30H106NS1	SAFETY LC E T4 R30 H1060 D4-12M SLAVE1	-
XUSL4E30H106NS2	SAFETY LC E T4 R30 H1060 D4-12M SLAVE2	-
XUSL4E30H121NTQ	SAFETY LIGHT CURTAIN H=1210MM E T4 R30 D4-12M BULK PACKAGING MOQ25	-
XUSL4E30H181LWH	XUSL type 4 Hand IP69K with Heating – Long Sensing Range - Hp = 1810 mm, R=30mm	-
XUSL4E3BB081LWH	SAFETY LC E T4 3B H810 D8-17M IP69H	-
XUSL4E3BB081NM	SAFETY LC E T4 3B H810 D4-12M MASTER	-
XUSL4E3BB081NS1	SAFETY LC E T4 3B H810 D4-12M SLAVE1	-
XUSL4E3BB081NS2	SAFETY LC E T4 3B H810 D4-12M SLAVE2	-
XUSL4E4BB091LWC	SAFETY LC E T4 4B H910 D8-17M IP69	-
XUSL4E4BB091NM	SAFETY LC E T4 4B H910 D4-12M MASTER	-
XUSL4E4BB091NS1	SAFETY LC E T4 4B H910 D4-12M SLAVE1	-
XUSL4E4BB091NS2	SAFETY LC E T4 4B H910 D4-12M SLAVE2	-
XUSL4MA30H076N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 R30 H=76CM D4-12M	-
XUSL4MA30H106N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 R30 H106CM D4-12M	-
XUSL4MA30H121N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 R30 H121CM D4-12M	-
XUSL4MA30H136N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 R30 H136CM D4-12M	-

TMSS France and its affiliates

Postal address / Adresse postale :
Tour Eqho 2 avenue Gambetta 92400 COURBEVOIE - France

Legal information / Mentions légales
Société par actions simplifiée au capital de 366 931 214 euros
908 125 255 RCS Nanterre – code APE : 2640Z
Siret : 90812525500012
n° ident. TVA : FR 21 908 125 255
Siège Social : Tour Eqho - 2 avenue Gambetta - 92400 COURBEVOIE – France

XUSL4MA40H091N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 R40 H 91CM D4- 12M	-
XUSL4MA40H106N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 R40 H106CM D4-12M	-
XUSL4MA40H166N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 R40 H166CM D4-12M	-
XUSL4MA40H181N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 R40 H181CM D4-12M	-
XUSL4MA40H196N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 R40 H196CM D4-12M	-
XUSL4MA40H211N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE/SOFT CONFIG T4 R40 H211CM D4-12M	-
XUSL4MB30H061N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 R30 H=61CM D4-12M	-
XUSL4MB30H076N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 R30 H=76CM D4-12M	-
XUSL4MB30H091N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 R30 H=91CM D4-12M	-
XUSL4MB30H106N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 R30 H=106CM D4- 12M	-
XUSL4MB30H121N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 R30 H=121CM D4- 12M	-
XUSL4MB30H151N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 R30 H=151CM D4- 12M	-
XUSL4MB40H121N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 R40 H=121CM D4- 12M	-
XUSL4MB40H136N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 R40 H=136CM D4- 12M	-
XUSL4MB40H151N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 R40 H=151CM D4- 12M	-
XUSL4MB40H166N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 R40 H=166CM D4- 12M	-
XUSL4MB40H196N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 R40 H=196CM D4- 12M	-
XUSL4MB40H211N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 R40 H=211CM D4- 12M	-
XUSL4MB40H226N	SAFETY LIGHT CURTAIN INTEGRATED MUTING HARDWARE CONFIG T4 R40 H=226CM D4- 12M	-
XUSL4P30H031N	SAFETY LIGHT CURTAIN H=310MM	-
XUSL4P30H061N	SAFETY LIGHT CURTAIN H=610MM P T4 R30 D4	-
XUSL4T30H016SIT	TYPE 4 30mm HANDS 160MM app. TESSILE	-
XUSL4T30H026SIT	TYPE 4 30mm HANDS 260MM app. TESSILE	-
XUSL4T30H046SIT	TYPE 4 30mm HANDS 460MM app. TESSILE	-
XUSL2E30H061NTQ	Safety light curtain type 2, XUSL Hand protection, Std sensing range, Hp = 610 mm, R=30 mm, MOQ=25pcs	-
XUSL2E30H091NTQ	Safety light curtain type 2, XUSL Hand protection, Std sensing range, Hp = 910 mm, R=30 mm, MOQ=25pcs	-
XUSL2E30H121NTQ	Safety light curtain type 2, XUSL Hand protection, Std sensing range, Hp = 1210 mm, R=30 mm, MOQ=25pcs	-
XUSZAML2PTS	SAFETY LIGHT CURTAIN MUTING ARM L 2PARALLEL MULTI-BEAMS HIGH SPEED CONVEYOR	-
XUSZAMT2XT	SAFETY LIGHT CURTAIN MUTING ARM T 2CROSSED MULTI-BEAMS	-
XUSZAMT4PT	SAFETY LIGHT CURTAIN MUTING ARMS T 4PARALLEL MULTI-BEAMS	-
XUSZAMT4PTS	SAFETY LIGHT CURTAIN MUTING ARM T 4P MULTI-BEAMS HIGH SPEED CONVEYOR	-
XUSZASL2PPS	SAFETY LIGHT CURTAIN MUTING ARM L 2PARALLEL SINGLE BEAM HIGH SPEED CONVEYOR	-
XUSZASL2PPT	SAFETY LIGHT CURTAIN MUTING ARM L 2PARALLEL SINGLE BEAM TRANSPARENT MATERIAL	-
XUSZAST4PPS	SAFETY LIGHT CURTAIN MUTING ARM T 4PARALLEL SINGLE BEAM HIGH SPEED CONVEYOR	-
XUSZAST4PPT	SAFETY LIGHT CURTAIN MUTING ARM T 4PARALLEL SINGLE BEAM TRANSPARENT MATERIAL	-
XUSZBMC6	SET OF 6ADJUSTABLE FASTENING BRACKETS FOR SAFETY LIGHT CURTAIN INTEGRATED MUTING	-

TMSS France and its affiliates

Postal address / Adresse postale :
Tour Eqho 2 avenue Gambetta 92400 COURBEVOIE - France

Legal information / Mentions légales
Société par actions simplifiée au capital de 366 931 214 euros
908 125 255 RCS Nanterre – code APE : 2640Z
Siret : 90812525500012
n° ident. TVA : FR 21 908 125 255
Siège Social : Tour Eqho - 2 avenue Gambetta - 92400 COURBEVOIE – France

XUSZMD016	SAFETY _LC DEFLECTIVE MIRROR PH 160MM	-
XUSZMF138	SAFETY _LC COLUMN WITH MIRROR 1385MM	-
XUSZPM5BXPLO9	MULTIBEAMS SENSORS FOR MUTING ARM B CODING	-
XUSZSC105R	SAFETY _LC COLUMN W _O MIRROR 1055MM PG11	-
XUSZSC172R	SAFETY _LC COLUMN W _O MIRROR 1725MM PG11	-
XUSZSM166	COLUMN FOR SAFETY LIGHT CURTAIN INTEGRATED MUTING UP TO 166 CM PROTECTED HEIGHT	-
XUSZSM2B	COLUMN FOR 2 BEAMS SAFETY LIGHT CURTAIN INTEGRATED MUTING	-
XUSZTR40	SAFETY LIGHT CURTAIN TEST ROD DIAMETER 40MM	-
XUSZWPE015	SAFETY _LC PROTECTIVE SCREEN 150mm	-
XUSZWPE030	SAFETY _LC PROTECTIVE SCREEN 300mm	-
XUSZWPE050	SAFETY LIGHT CURTAIN PROTECTIVE SCREEN 510MM 2 BEAMS	-
XUSZWPE080	SAFETY LIGHT CURTAIN PROTECTIVE SCREEN 810MM 3 BEAMS	-
XUSZWPE090	SAFETY _LC PROTECTIVE SCREEN 900mm	-
XUSZWPE105	SAFETY _LC PROTECTIVE SCREEN 1050mm	-
XUSZWPE165	SAFETY _LC PROTECTIVE SCREEN 1650mm	-
XUSZSC202	SAFETY _LC COLUMN W _O MIRROR 2025MM	-
XUSZBSS4	SAFETY _LC SWIVELLING BRACKETS x4	-
XUSZLPE	SAFETY _LC LASER POINTER FOR MODELS E	-
XUSZFB2	SAFETY _LC FIXING BASE 2 PLATES	-
XUSZSS125	SAFETY _LC SPL COLUMN W _O MIRROR 1255MM	-
XUSZSC138	SAFETY _LC COLUMN W _O MIRROR 1385MM	-
XUSZBSC4	SAFETY _LC CURVED BRACKETS x4	-
XUSZFB1	SAFETY _LC FIXING BASE 1 PLATE	-
XUSZMF202	SAFETY _LC COLUMN WITH MIRROR 2025MM	-
XUSZMD061	SAFETY _LC DEFLECTIVE MIRROR PH 610MM/2B	-
XUSZMD046	SAFETY _LC DEFLECTIVE MIRROR PH 460MM	-
XUSZASL2XT	SAFETY LIGHT CURTAIN MUTING ARM L2CROSSED SINGLE BEAM	-
XUSZMD076	SAFETY _LC DEFLECTIVE MIRROR PH 760MM	-
XUSZAML2XP	SAFETY LIGHT CURTAIN MUTING ARM L 2 PARALLEL MULTI-BEAMS	-
XUSZAST4PP	SAFETY LIGHT CURTAIN MUTING ARM T 4PARALLEL SINGLE BEAM	-
XUSZMD091	SAFETY _LC DEFLECTIVE MIRROR PH 910MM/3B	-
XUSZAST2XT	SAFETY LIGHT CURTAIN MUTING ARM T 2CROSSED SINGLE BEAM	-
XUSZMD121	SAFETY _LC DEFLECTIVE MIRROR PH 1210MM	-
XUSZMD151	SAFETY _LC DEFLECTIVE MIRROR PH 1510MM	-
XUSZTR14	SAFETY _LC TEST ROD DIAM14MM	-
XUSZMD181	SAFETY _LC DEFLECTIVE MIRROR PH 1810MM	-
XUSZMF125	SAFETY _LC COLUMN WITH MIRROR 1255MM	-
XUSZSC138R	SAFETY _LC COLUMN W _O MIRROR 1385MM PG11	-
XUSZMD166	SAFETY _LC DEFLECTIVE MIRROR PH 1660MM	-
XUSZSC172	SAFETY _LC COLUMN W _O MIRROR 1725MM	-
XUSZVA8	SAFETY _LC SHOCK _ABSORBERx8	-
XUSZASL2PP	SAFETY LIGHT CURTAIN MUTING ARM L2PARALLEL SINGLE BEAM	-
XUSZTR30	SAFETY _LC TEST ROD DIAM30MM	-
XUSZBSKSSE	LIGHT CURTAIN MOUNTING ACCESSORIES KIT S	-
XUSZWPEFC	SAFETY _LC PROTECTIVE SCREEN FIX CLAMPS	-
XUSZSC202R	SAFETY _LC COLUMN W _O MIRROR 2025MM PG11	-
XUSZSM3B	COLUMN FOR 3 BEAMS SAFETY LIGHT CURTAIN INTEGRATED MUTING	-
XUSZSM136	COLUMN FOR SAFETY LIGHT CURTAIN INTEGRATED MUTING UP TO 136 CM PROTECTED HEIGHT	-
XUSZVA12	SAFETY _LC SHOCK _ABSORBERx12	-
XUSZMD106	SAFETY _LC DEFLECTIVE MIRROR PH 1060MM/4B	-
XUSZBSC6	SAFETY _LC CURVED BRACKETS x6	-
XUSZMD136	SAFETY _LC DEFLECTIVE MIRROR PH 1360MM	-
XUSZMF172	SAFETY _LC COLUMN WITH MIRROR 1725MM	-
XUSZSC105	SAFETY _LC COLUMN W _O MIRROR 1055MM	-
XUSZSM4B	COLUMN FOR 4 BEAMS SAFETY LIGHT CURTAIN INTEGRATED MUTING	-
XUSZVA4	SAFETY _LC SHOCK _ABSORBERx4	-
XUSZBMC4	SET OF 4ADJUSTABLE FASTENING BRACKETS FOR SAFETY LIGHT CURTAIN INTEGRATED MUTING	-
XUSZWPE060	SAFETY _LC PROTECTIVE SCREEN 600mm	-
XUSZMD031	SAFETY _LC DEFLECTIVE MIRROR PH 310MM	-
XUSZWPE045	SAFETY _LC PROTECTIVE SCREEN 450mm	-
XUSZWPE075	SAFETY _LC PROTECTIVE SCREEN 750mm	-
XUSZWPE180	SAFETY _LC PROTECTIVE SCREEN 1800mm	-
XUSZPM5AXPLO9	MULTIBEAMS SENSORS FOR MUTING ARM A CODING	-
XUSZWPE120	SAFETY _LC PROTECTIVE SCREEN 1200mm	-

TMSS France and its affiliates

Postal address / Adresse postale :
Tour Eqho 2 avenue Gambetta 92400 COURBEVOIE - France

Legal information / Mentions légales
Société par actions simplifiée au capital de 366 931 214 euros
908 125 255 RCS Nanterre – code APE : 2640Z
Siret : 90812525500012
n° ident. TVA : FR 21 908 125 255
Siège Social : Tour Eqho - 2 avenue Gambetta - 92400 COURBEVOIE – France

XUSZWPE091	SAFETY LIGHT CURTAIN PROTECTIVE SCREEN 910MM 4 BEAMS	-	
XUSZWPE150	SAFETY_LC PROTECTIVE SCREEN 1500mm	-	
In this product, no substance under REACH annex XVII regulation is used in the scope of restriction. According to REACH Regulation EC 1907/2006 article 33 duties and the judgment of the EU court of Justice of 10 September 2015 in case C-106/14, the following SVHC(s) are present in this product above 0.1% threshold at part level. Our products are safe from a chemical exposure perspective, under normal condition of use.			
SvHC Content	CAS Number	EC Number	Specific Safe Condition of Use
None	None	None	None

TMSS France and its affiliates

Postal address / Adresse postale :
Tour Eqho 2 avenue Gambetta 92400 COURBEVOIE - France

Legal information / Mentions légales
Société par actions simplifiée au capital de 366 931 214 euros
908 125 255 RCS Nanterre – code APE : 2640Z
Siret : 90812525500012
n° ident. TVA : FR 21 908 125 255
Siège Social : Tour Eqho - 2 avenue Gambetta - 92400 COURBEVOIE – France