

## Features

Use: Indoor  
Type of installation: RECESSED INTO PLASTERBOARD  
Emission: DIRECT  
Optics: SPOT  
Beam: 36°  
Colour: WHITE  
Dimming: WITH ACCESSORY  
Emergency: WITH ACCESSORY  
L: 123mm  
A: 123mm  
H: 114mm  
Warranty: 5 years  
Weight: 0.97kg

## Tech data

Luminaire luminous flux: 2908lm  
Luminous flux in emergency: 24%  
IP: 20  
Insulation class: III  
Supply voltage: DC 700 MA  
SELV: No

## Source

Light source: LED  
Source power: 26W  
Colour temperature: 4000K  
CRI: >90  
LED lifespan: 30000h L70 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

## Standards


Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

## ELECTRICAL ACCESSORIES

---




ALIM. LED MAX 30W 700MA

**101311.99**

## DIMMABLE ACCESSORIES

---




ALIM. LED MAX 40W 700MA 1-10V DALI PUSH

**101312.99**


## EMERGENCY ACCESSORIES

---



KIT EMERGENZA 1H 9V-58V

**18002.99**



KIT EMERGENZA 3H 9V-58V

**18003.99**