



## Features

Use: Indoor  
Type of installation: TRACK  
Emission: DIRECT  
Optics: SPOT  
Beam: 34°  
Colour: BLACK  
Dimming: DALI  
Emergency: NO  
L: 166mm  
A: Ø 55mm  
H: 60mm  
Made in: ITALY  
Warranty: 5 years

## Tech data

Luminaire input power: 15W  
Luminaire luminous flux: 1226lm  
IP: 20  
Insulation class: III  
Supply voltage: 48 Vdc  
SELV: Si

## Source

Light source: LED  
Source power: 13W  
Source luminous flux: 1520lm  
Colour temperature: 4000K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

## Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)