

## Features

Use: Indoor  
Type of installation: RECESSED INTO PLASTERBOARD  
Emission: DIRECT  
Optics: SPOT  
Beam: 30°  
Colour: WHITE  
Dimming: ON/OFF  
Emergency: WITH ACCESSORY  
A: Ø85mm  
H: 50mm  
D: 72-74mm  
Warranty: 5 years  
Weight: 0.255kg

## Tech data

Luminaire input power: 4W  
Luminaire luminous flux: 310lm  
IP: 20  
Insulation class: II  
Supply voltage: 220-240V 50/60Hz  
UGR: <19  
SELV: No

## Source

Light source: LED  
Source power: 3W  
Colour temperature: 4000K  
CRI: >80  
LED lifespan: 30000h L70 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2


## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)

## EMERGENCY ACCESSORIES


---



KIT EMERGENZA 1H 9V-58V

**18002.99**

---



KIT EMERGENZA 3H 9V-58V

**18003.99**

---