



THE PANEL 2

102002.01

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor

Type of installation: RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED

Emission: DIRECT

Optics: OPAL

Colour: WHITE

Dimming: ON/OFF

Emergency: WITH ACCESSORY

L: 595mm

A: 595mm

H: 10mm

Warranty: 5 years

Weight: 2.8kg

Tech data

Luminaire input power: 39W

Luminaire luminous flux: 3447lm

Luminous flux in emergency: 1h: 12% / 3h: 5%

IP: 40

Insulation class: II

No. of driver per product: 1

Supply voltage: 950mA aliment.incluso

UGR: <19 4H-8H S=0,25

IK: IK07

SELV: Sì

Source

Light source: LED

Source power: 35W

Source luminous flux: 4155lm

Colour temperature: 4000K

CRI: >80

Colour tolerance: 3 Step MacAdam

LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

[View more product info](#)










Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 14/11/2024, 18:27:58

THE PANEL 2

102002.01


MOUNTING ACCESSORIES

	BOX PER INST. PLAFONE THE PANEL 600X600	102086.01
	THE PANEL: STAFFE PLAFONE 600/1200	16213.99
	THE PANEL 2: KIT PER BIN.600X600 3P	102053.01
	THE PANEL: N.4 SOSP. SNODATE L3000	16230.99
	THE PANEL 2: KIT INST.INC.RAS.CART.600	102028.99
	THE PANEL: KIT MOLLE INC.CART.600/1200	16215.99
	THE PANEL: N.2 GIUNTI+N.2 SOSPL3000 AN.	16227.96
	KIT ALIMENTAZIONE L1200 3P BIA	108919.01
	THE PANEL: N.2 GIUNTI NON SOSPESI	16232.96
	THE PANEL: SNODO 600+N.2 SOSPL3000 BIA.	16228.01
	KIT ALIMENTAZIONE L3000 3P BIA	108920.01
	THE PANEL 2: KIT ANTIC. L3000 +MORS.	102031.99



THE PANEL 2

102002.01




THE PANEL: N.2 GIUNTI SNODATI L3000 **16231.96**




THE PANEL: KIT SOSP.600/1200 CAVI 4X3MT **16223.99**

EMERGENCY ACCESSORIES



THE PANEL 2: EMER.INC.3H 10/54VDC **1020A5.99**



THE PANEL 2: EMER.INC.1H 10/54VDC **1020A4.99**

