

Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: SPOT
Beam: 36°
Colour: BLACK
Dimming: WITH ACCESSORY
Emergency: WITH ACCESSORY
H: 85mm
ø: Ø50
D: 45mm
Warranty: 5 years
Weight: 0.17kg

Tech data

Luminaire luminous flux: 568lm
Luminous flux in emergency: 1h: 63% / 3h: 25%
IP: 20
Insulation class: III
Supply voltage: DC 350 mA
UGR: <19
SELV: No

Source

Light source: LED
Source power: 7W
Source luminous flux: 662lm
Colour temperature: 3000K
CRI: >90
LED lifespan: 30000h L70 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 1
Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)



ELECTRICAL ACCESSORIES

	ALIM. LED 15W 350MA/2-42V	101330.99
	ALIM. LED MAX 10W 350MA	103606.99
	ALIM. LED MAX 18W 350MA	101326.99
	ALIM. LED MAX 15W 350MA	101310.99

DIMMABLE ACCESSORIES

	ALIM. LED 25W 350MA/2-50V DALI/PUSH	101333.99
	ALIM. MAX.16W/350MA DALI/PUSH/0-10/1-10	103605.99

EMERGENCY ACCESSORIES

	KIT EMERGENZA 3H 10V-54V	18005.99
	KIT EMERGENZA 1H 10V-54V	18004.99