




Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: SPOT
Beam: 36°
Colour: WHITE
Dimming: WITH ACCESSORY
Emergency: WITH ACCESSORY
H: 85mm
ø: Ø50
D: 45mm
Warranty: 5 years
Weight: 0.17kg

Tech data

Luminaire luminous flux: 532lm
Luminous flux in emergency: 1h: 63% / 3h: 25%
IP: 20
Insulation class: III
Supply voltage: DC 350 mA
SELV: No



Source

Light source: LED
Source power: 7W
Colour temperature: 2700K
CRI: >90
LED lifespan: 30000h

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[KONE: View more product info](#)

ELECTRICAL ACCESSORIES



ALIM. LED 15W 350MA/2-42V

101330.99



ALIM. LED MAX 18W 350MA

101326.99

DIMMABLE ACCESSORIES



ALIM. LED 25W 350MA/2-50V DALI/PUSH

101333.99

EMERGENCY ACCESSORIES



KIT EMERGENZA 3H 10V-54V

18005.99



KIT EMERGENZA 1H 10V-54V

18004.99