



GHOST EVO

104040.02

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor
Emission: ADJUSTABLE
Optics: SPOT
Beam: 15 - 38°
Colour: BLACK
Dimming: WITH ACCESSORY
Emergency: NO
H: 166mm
ø: Ø72
Warranty: 5 years
Weight: 1.0kg

Tech data

Luminaire luminous flux: 1916 - 2037lm
IP: 20
Insulation class: III
Supply voltage: DC 600 mA

Source

Light source: LED
Source power: 23W
Source luminous flux: 2638lm
Colour temperature: 4000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 30000h L70 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 14/11/2024, 18:28:06

COMPLETION ACCESSORIES



ALETTE SAGOM. GHOST/SPYGLASS D=72 NER

104043.02



HONEYCOMB PER GHOST E SPYGLASS D=72 NERO

104042.02

ELECTRICAL ACCESSORIES



GHOST EVO: ALIM. LED 600MA 10/45V

104041.99

DIMMABLE ACCESSORIES



ALIM. LED DALI/PUSH 24.5W/550MA 20-45V

101324.99



ALIM. LED 25W 600MA/2-42V DALI/PUSH

101335.99