



## Features

Use: Indoor

Type of installation: RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED

Emission: DIRECT

Optics: LENS UGR<19

Colour: WHITE

Dimming: ON/OFF

Emergency: WITH ACCESSORY

L: 1125mm

A: 295mm

H: 14 (30 con alim.)mm

Warranty: 5 years

Weight: 3.37kg

## Tech data

Luminaire input power: 33W

Luminaire luminous flux: 4100lm

Luminous flux in emergency: 1h: 13% / 3h: 5%

IP: 40

Insulation class: II

No. of driver per product: 1

Supply voltage: 900 mA ALIMENT.INCLUSO

UGR: <19

SELV: Si

## Source

Light source: LED

Source power: 30W

Source luminous flux: 5016lm

Colour temperature: 4000K

CRI: >90

LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

## Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2011).

[View more product info](#)



## MOUNTING ACCESSORIES

	<p>SCHOOL: KIT MOLLE PER INCASSO</p>	<p>104107.99</p>
	<p>SCHOOL: KIT ANTICADUTA L=3000</p>	<p>104119.99</p>
	<p>KIT ALIMENTAZIONE L1200 3P BIA</p>	<p>108919.01</p>
	<p>BOX PER INST. PLAFONE THE PANEL 1200X300</p>	<p>102087.01</p>
	<p>SCHOOL: KIT INST.PLAFONE 1200X300</p>	<p>104109.01</p>
	<p>THE PANEL 2: KIT INST.INC.RAS.CART.1200</p>	<p>102029.99</p>
	<p>SCHOOL: KIT SOSPENSIONE H1200</p>	<p>104110.99</p>

## EMERGENCY ACCESSORIES

	<p>THE PANEL 2: EMER.INC.3H 10/54VDC</p>	<p>1020A5.99</p>
	<p>THE PANEL 2: EMER.INC.1H 10/54VDC</p>	<p>1020A4.99</p>