

## Features

Use: Indoor

Type of installation: RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED

Emission: DIRECT

Optics: LENS UGR<19

Colour: WHITE

Dimming: PUSH, DALI

Emergency: WITH ACCESSORY

L: 1125mm

A: 295mm

H: 14 (35 con alim.)mm

Warranty: 5 years

Weight: 3.37kg

## Tech data

Luminaire input power: 33W

Luminaire luminous flux: 4100lm

Luminous flux in emergency: 20%

IP: 40

Insulation class: I

Supply voltage: 900 mA ALIMENT.INCLUSO

UGR: <19

SELV: Si

## Source

Light source: LED

Source power: 30W

Source luminous flux: 5016lm

Colour temperature: 4000K

CRI: >90

LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.


CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

## Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2011).


[View more product info](#)

## MOUNTING ACCESSORIES




SCHOOL: KIT INST.PLAFONE 1200X300

104109.01




SCHOOL: KIT MOLLE PER INCASSO

104107.99




SCHOOL: KIT SOSPENSIONE H1200

104110.99



KIT ALIMENTAZIONE L1200 5P BIA

108921.01



THE PANEL 2: KIT INST.INC.RAS.CART.1200

102029.99



SCHOOL: KIT ANTICADUTA L=3000

104119.99