



Features

Use: Indoor
Type of installation: WALL, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL
Colour: WHITE
Dimming: ON/OFF
Emergency: NO
L: Ø280mm
H: 48mm
Warranty: 5 years
Weight: 0.937kg

Tech data

Luminaire input power: 23W
Luminaire luminous flux: 2036lm
IP: 44
Insulation class: II
No. of driver per product: 1
Supply voltage: 220-240V 50/60 Hz
SELV: No

Source

Light source: LED
Source power: 19W
Source luminous flux: 2450lm
Colour temperature: 4000K
CRI: >90
LED lifespan: 50000h

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

LUNA

104330.01

novalux
ITALIAN LIGHTING DESIGN SINCE 1948

DIMMABLE ACCESSORIES



LUNA: TELECOMANDO PER SET SENSORE

104335.99



Novalux S.r.l. via Marzabotto, 2 40050 Fano di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 14/11/2024, 18:24:31