




THE PANEL IP65

105502.01

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Altezza minima per installazione 60 mm
Minimum height for installation 60 mm



Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL
Colour: WHITE
Dimming: ON/OFF
Emergency: NO
L: 595mm
A: 595mm
H: 11mm
Warranty: 5 years
Weight: 2.8kg

Tech data

Luminaire input power: 40W
Luminaire luminous flux: 4137lm
IP: 65
Insulation class: II
Supply voltage: 220-240V 50/60Hz
IK: IK09
SELV: Si

Source

Light source: LED
Source power: 36W
Source luminous flux: 5380lm
Colour temperature: 4000K
CRI: >80
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

[View more product info](#)





Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 14/11/2024, 18:27:54

THE PANEL IP65

105502.01

MOUNTING ACCESSORIES

	BOX PER INST. PLAFONE THE PANEL 600X600	102086.01
	THE PANEL 2: KIT INST.INC.RAS.CART.600	102028.99
	KIT ALIMENTAZIONE L1200 3P BIA	108919.01
	THE PANEL IP65: KIT ANTIC. L3000 +MORS.	105503.99
	KIT ALIMENTAZIONE L3000 3P BIA	108920.01
	ROTO: D=1200 KIT 4 SOSP. L3000	104429.99

