



P-30 PCB

105819.01

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: OPAL
Colour: WHITE
Dimming: ON/OFF
Emergency: NO
L: 1600mm
A: 31mm
H: 31mm
Made in: ITALY
Warranty: 5 years
Weight: 1.62kg

Tech data

Luminaire input power: 19.9W
Luminaire luminous flux: 1835lm
IP: 40
Insulation class: II
No. of driver per product: 1
Supply voltage: 0.5A alim. incluso 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 16W
Source luminous flux: 3149lm
Colour temperature: 4000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 14/11/2024, 18:29:57

P-30 PCB

105819.01

SCREENS



P-30: DIFF. OPALEPER L1600

103313.99



P-30: DIFF. OPALE L=6500

103315.99

COMPLETION ACCESSORIES



P-30: COPPIA TESTATE STRIP/INCASSO BIA

103316.01



P-30: ANGOLO L INCASSO BIANCO

103328.01



P-30: COVER ANGOLO L BIANCO

103329.01



P-30: ANGOLO T INCASSO BIANCO

103332.01



P-30: COVER ANGOLO T BIANCO

103333.01

