



Features

Use: Indoor
Type of installation: TRACK
Emission: ADJUSTABLE
Optics: SPOT
Beam: 38°
Colour: BLACK
Dimming: DALI
Emergency: NO
L: 110mm
A: Ø55mm
H: 150mm
Warranty: 5 years
Weight: 0.42kg

Tech data

Luminaire input power: 11.5W
Luminaire luminous flux: 1189lm
IP: 20
Insulation class: II
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 10W
Source luminous flux: 1426lm
Colour temperature: 4000K
CRI: >90
LED lifespan: 30000h

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[DALÌ: View more product info](#)

SCREENS



DALÌ : LENTE 55° PER 10W

106126.00



DALÌ : LENTE 15° PER 10W

106136.00

COMPLETION ACCESSORIES



DALÌ : INSERTO ORO OPACO PER 10W

106128.15



DALÌ : HONEYCOMB PER 10W

106127.02