



## Features

Use: Indoor  
Type of installation: FLOOR  
Emission: DIRECT/INDIRECT  
Optics: MICROPRISMATIZED  
Colour: WHITE  
Dimming: ROTARY DIMMER  
Emergency: NO  
L: 610mm  
A: 280mm  
H: 1950mm  
Warranty: 5 years  
Weight: 15kg

## Tech data

Luminaire input power: 86W  
Luminaire luminous flux: 6425lm  
Direct luminous flux: 2716lm  
Indirect luminous flux: 3708lm  
IP: 40  
Insulation class: I  
No. of driver per product: 1  
Supply voltage: 220-240V 50/60Hz  
UGR: <19  
SELV: No

## Source

Light source: LED  
Source power: 80W  
Source luminous flux: 8900lm  
Colour temperature: 4000K  
CRI: >90  
LED lifespan: 50000h L80 B10

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

