


Features

Use: Indoor
Type of installation: SUSPENDED
Emission: DIRECT/INDIRECT
Optics: OPAL
Colour: WHITE
Dimming: WITH ACCESSORY
Emergency: NO
L: Ø962mm
A: 40mm
H: 50mm
Made in: ITALY
Warranty: 5 years
Weight: 6.9kg


Tech data

Luminaire input power: 141.5W
Luminaire luminous flux: 13482lm
Direct luminous flux: 5246lm
Indirect luminous flux: 8236lm
IP: 40
Insulation class: III
Supply voltage: MAX 1.8A
UGR: <19
IK: 3
SELV: Si



Source

Light source: LED
Source power: 124W
Source luminous flux: 19212lm
Colour temperature: 4000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20



Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[HALOS B ACOUSTIC: View more product info](#)


[HALOS B: View more product info](#)




MOUNTING ACCESSORIES

	HALOS: ROSONE ALIM. REMOTA BIA	105157.01
	HALOS: ROSONE DOPPIA ALIM. REMOTA BIA	105158.01

ELECTRICAL ACCESSORIES

	HALOS-B: COPPIA ALIM. ON/OFF REM.	107125.99
	HALOS-B: ROSONE ALIM. ON/OFF BI	107127.01
	HALOS-B: ROSONE-N ALIM. ON/OFF BIA	107129.01

DIMMABLE ACCESSORIES

	HALOS-B: COPPIA ALIM. DALI/PUSH REM.	107126.99
	HALOS-B: ROSONE ALIM. DALI/PUSH BI	107128.01
	HALOS-B: ROSONE-N ALIM. D/PUSH BI	107130.01