



FORTY8 TRACK

108527.02

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor
Type of installation: TRACK
Emission: DIRECT
Optics: SPOT
Beam: 35°
Colour: BLACK
Dimming: DALI
Emergency: NO
H: 400mm
ø: Ø26
Warranty: 5 years
Weight: 0.33kg

Tech data

Luminaire input power: 9W
Luminaire luminous flux: 518lm
IP: 20
Insulation class: III
No. of driver per product: 1
Supply voltage: 48 Vdc
SELV: Si

Source

Light source: LED
Source power: 7W
Colour temperature: 4000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 30000h L70 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 14/11/2024, 18:23:40

FORTY8 TRACK

108527.02

novalux
ITALIAN LIGHTING DESIGN SINCE 1948

SCREENS



MINITUBE F8: DIFFUSORE OPALE L=100MM

108528.99



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 14/11/2024, 18:23:40