

## Features

Use: Indoor  
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK  
Emission: DIRECT  
Optics: OPAL  
Colour: WHITE  
Dimming: PUSH, DALI  
Emergency: NO  
L: 1680mm  
A: 53mm  
H: 69mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 4.2kg

## Tech data

Luminaire input power: 40.5W  
Luminaire luminous flux: 2913lm  
IP: 40  
Insulation class: I  
No. of driver per product: 1  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

## Source

Light source: LED  
Source power: 36W  
Colour temperature: 3000K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

# HERO

108649.01 + 108903.99

HERO: 36W 3K 1680 DALI BIA + HERO: DIFF. OPALE PER 1680



**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948




## Features

Use: Indoor  
Optics: OPAL  
L: 1680mm  
A: 48mm  
H: 6mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 0.4kg

## Tech data

IP: 40



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 14/11/2024, 19:17:38

## COMPLETION ACCESSORIES

|                                                                                     |                                |           |
|-------------------------------------------------------------------------------------|--------------------------------|-----------|
|    | HERO: MOD.CIECO ANG.SX 150 BIA | 108677.01 |
|    | HERO: MOD.CIECO 1680 BIA       | 108681.01 |
|    | HERO: MOD.CIECO 1400 BIA       | 108680.01 |
|    | HERO: COPPIA TESTATE BIA       | 108684.01 |
|    | HERO: MOD.CIECO 250 BIA        | 108676.01 |
|  | HERO: MOD.CIECO 1120 BIA       | 108679.01 |
|  | HERO: MOD.CIECO ANG.DX 150 BIA | 108678.01 |

## MOUNTING ACCESSORIES

|                                                                                                   |                                 |           |
|---------------------------------------------------------------------------------------------------|---------------------------------|-----------|
|                | KIT ALIMENTAZIONE L1200 5P BIA  | 108921.01 |
|                | HERO: SOSPL3000 1PZ. TESTA/CODA | 108685.99 |
|                | KIT ALIMENTAZIONE L3000 5P BIA  | 108922.01 |
|  | HERO: STAFFA PARETE "L" BIA     | 108687.01 |



HERO: SPESS. CARTONG. 10MM 2PZ.

108689.99



HERO: SOSPL3000 1PZ. UNIONE

108686.99



ALL-TRACK: COPPIA ADATT. 3P+DALI BIA

106723.01



HERO: SOSPL3000 1PZ TESTA W.G.ALTO

1086A1.99



HERO: KIT INCASSO LED (1X)

108688.99



HERO: SOSPL3000 1PZ UNIONE W.G.ALTO

1086A2.99