



Features

Use: Indoor
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK
Emission: DIRECT
Optics: OPAL
Colour: CAFFE
Dimming: PUSH, DALI
Emergency: NO
L: 1960mm
A: 53mm
H: 69mm
Made in: ITALY
Warranty: 5 years
Weight: 5kg

Tech data

Luminaire input power: 48.3W
Luminaire luminous flux: 3398lm
IP: 40
Insulation class: I
No. of driver per product: 2
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 42W
Colour temperature: 3000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

HERO

108650.20 + 108904.99

HERO: 42W 3K 1960 DALI CAF + HERO: DIFF. OPALE PER 1960



novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor
Optics: OPAL
L: 1960mm
A: 48mm
H: 6mm
Made in: ITALY
Warranty: 5 years
Weight: 0.4kg

Tech data

IP: 40



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 14/11/2024, 19:05:53

COMPLETION ACCESSORIES

 Technical drawing of a linear light fixture, model MOD.CIECO 250 CAF. It shows a side view with dimensions: H 135, L 250, W 33. A top view shows a rectangular profile.	HERO: MOD.CIECO 250 CAF	108676.20
 Technical drawing of a linear light fixture, model MOD.CIECO 1400 CAF. It shows a side view with dimensions: H 135, L 1400, W 33. A top view shows a rectangular profile.	HERO: MOD.CIECO 1400 CAF	108680.20
 Technical drawing of an angled linear light fixture, model MOD.CIECO ANG.SX 150 CAF. It shows a side view with dimensions: H 135, L 150, W 33. A top view shows an L-shaped profile.	HERO: MOD.CIECO ANG.SX 150 CAF	108677.20
 Technical drawing of a linear light fixture, model MOD.CIECO 1680 CAF. It shows a side view with dimensions: H 135, L 1680, W 33. A top view shows a rectangular profile.	HERO: MOD.CIECO 1680 CAF	108681.20
 Technical drawing of a pair of end caps, model COPPIA TESTATE CAF. It shows two small rectangular components with dimensions: L 33, W 33.	HERO: COPPIA TESTATE CAF	108684.20
 Technical drawing of an angled linear light fixture, model MOD.CIECO ANG.DX 150 CAF. It shows a side view with dimensions: H 135, L 150, W 33. A top view shows an L-shaped profile.	HERO: MOD.CIECO ANG.DX 150 CAF	108678.20
 Technical drawing of a linear light fixture, model MOD.CIECO 1120 CAF. It shows a side view with dimensions: H 135, L 1120, W 33. A top view shows a rectangular profile.	HERO: MOD.CIECO 1120 CAF	108679.20

MOUNTING ACCESSORIES

 Technical drawing of a power supply kit, model KIT ALIMENTAZIONE L1200 5P BIA. It shows a cable with a connector and dimensions: L 1200.	KIT ALIMENTAZIONE L1200 5P BIA	108921.01
 Technical drawing of a power supply kit, model HERO: SOSPL3000 1PZ. TESTA/CODA. It shows a cable with a connector and dimensions: L 3000.	HERO: SOSPL3000 1PZ. TESTA/CODA	108685.99
 Technical drawing of a power supply kit, model KIT ALIMENTAZIONE L3000 5P BIA. It shows a cable with a connector and dimensions: L 3000.	KIT ALIMENTAZIONE L3000 5P BIA	108922.01
 Technical drawing of a power supply kit, model KIT ALIMENTAZIONE L3000 5P CAF. It shows a cable with a connector and dimensions: L 3000.	KIT ALIMENTAZIONE L3000 5P CAF	108922.20



HERO: SPESS. CARTONG. 10MM 2PZ.

108689.99



HERO: SOSP.L3000 1PZ. UNIONE

108686.99



ALL-TRACK: COPPIA ADATT. 3P+DALI NER

106723.02



HERO: STAFFA PARETE "L" CAF

108687.20



ALL-TRACK: COPPIA ADATT. 3P+DALI BIA

106723.01



HERO: SOSP.L3000 1PZ TESTA W.G.ALTO

1086A1.99



KIT ALIMENTAZIONE L1200 5P CAF

108921.20



HERO: KIT INCASSO LED (1X)

108688.99



HERO: SOSP.L3000 1PZ UNIONE W.G.ALTO

1086A2.99