



Features

Use: Indoor
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK
Emission: DIRECT
Optics: SPOT
Beam: 34°
Colour: CAFFE
Dimming: ON/OFF
Emergency: NO
L: 1120mm
A: 53mm
H: 69mm
Made in: ITALY
Warranty: 5 years
Weight: 3.4kg

Tech data

Luminaire input power: 29W
Luminaire luminous flux: 2230lm
IP: 40
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 2X13W
Source luminous flux: 2750lm
Colour temperature: 3000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



COMPLETION ACCESSORIES

 Diagram showing a cross-section of the HERO: MOD.CIECO 250 CAF track. Dimensions: H 135, L 250, W 33.	HERO: MOD.CIECO 250 CAF	108676.20
 Diagram showing a cross-section of the HERO: MOD.CIECO 1400 CAF track. Dimensions: H 135, L 1400, W 33.	HERO: MOD.CIECO 1400 CAF	108680.20
 Diagram showing a cross-section of the HERO: MOD.CIECO ANG.SX 150 CAF track. Dimensions: H 135, L 150, W 33.	HERO: MOD.CIECO ANG.SX 150 CAF	108677.20
 Diagram showing a cross-section of the HERO: MOD.CIECO 1680 CAF track. Dimensions: H 135, L 1680, W 33.	HERO: MOD.CIECO 1680 CAF	108681.20
 Diagram showing a cross-section of the HERO: COPPIA TESTATE CAF track. Dimensions: H 135, L 1680, W 33.	HERO: COPPIA TESTATE CAF	108684.20
 Diagram showing a cross-section of the HERO: MOD.CIECO ANG.DX 150 CAF track. Dimensions: H 135, L 150, W 33.	HERO: MOD.CIECO ANG.DX 150 CAF	108678.20
 Diagram showing a cross-section of the HERO: MOD.CIECO 1120 CAF track. Dimensions: H 135, L 1120, W 33.	HERO: MOD.CIECO 1120 CAF	108679.20

MOUNTING ACCESSORIES

 Diagram showing a cross-section of the HERO: SOSPL3000 1PZ. TESTA/CODA track. Dimensions: H 12, L 17.	HERO: SOSPL3000 1PZ. TESTA/CODA	108685.99
 Diagram showing a cross-section of the ALL-TRACK: COPPIA ADATT. 3P BIA track. Dimensions: H 135, L 1680, W 33.	ALL-TRACK: COPPIA ADATT. 3P BIA	106722.01
 Diagram showing a cross-section of the KIT ALIMENTAZIONE L1200 3P CAF track. Dimensions: H 135, L 1200, W 33.	KIT ALIMENTAZIONE L1200 3P CAF	108919.20
 Diagram showing a cross-section of the KIT ALIMENTAZIONE L1200 3P BIA track. Dimensions: H 135, L 1200, W 33.	KIT ALIMENTAZIONE L1200 3P BIA	108919.01



ALL-TRACK: COPPIA ADATT. 3P NER

106722.02

HERO: SPESS. CARTONG. 10MM 2PZ.

108689.99

HERO: SOSPL3000 1PZ. UNIONE

108686.99

HERO: STAFFA PARETE "L" CAF

108687.20

HERO: SOSPL3000 1PZ TESTA W.G.ALTO

1086A1.99

KIT ALIMENTAZIONE L3000 3P BIA

108920.01

HERO: KIT INCASSO LED (1X)

108688.99

HERO: SOSPL3000 1PZ UNIONE W.G.ALTO

1086A2.99

KIT ALIMENTAZIONE L3000 3P CAF

108920.20