



Features

Use: Indoor
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK
Emission: DIRECT
Optics: SPOT
Beam: 34°
Colour: CAPPUCCINO
Dimming: PUSH, DALI
Emergency: NO
L: 1120mm
A: 53mm
H: 69mm
Made in: ITALY
Warranty: 5 years
Weight: 3.4kg

Tech data

Luminaire input power: 29W
Luminaire luminous flux: 2464lm
IP: 40
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 2X13W
Source luminous flux: 3040lm
Colour temperature: 4000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

COMPLETION ACCESSORIES



HERO: MOD.CIECO ANG.SX 150 CAP

108677.21



HERO: MOD.CIECO 1120 CAP

108679.21



HERO: MOD.CIECO 1680 CAP

108681.21



HERO: COPPIA TESTATE CAP

108684.21



HERO: MOD.CIECO 1400 CAP

108680.21



HERO: MOD.CIECO 250 CAP

108676.21



HERO: MOD.CIECO ANG.DX 150 CAP

108678.21

MOUNTING ACCESSORIES



KIT ALIMENTAZIONE L1200 5P BIA

108921.01



HERO: SOSP.L3000 1PZ. TESTA/CODA

108685.99



KIT ALIMENTAZIONE L3000 5P BIA

108922.01



HERO: SPESS. CARTONG. 10MM 2PZ.

108689.99

	HERO: SOSP.L3000 1PZ. UNIONE	108686.99
	ALL-TRACK: COPPIA ADATT. 3P+DALI NER	106723.02
	KIT ALIMENTAZIONE L1200 5P CAP	108921.21
	ALL-TRACK: COPPIA ADATT. 3P+DALI BIA	106723.01
	HERO: SOSP.L3000 1PZ TESTA W.G.ALTO	1086A1.99
	HERO: KIT INCASSO LED (1X)	108688.99
	KIT ALIMENTAZIONE L3000 5P CAP	108922.21
	HERO: SOSP.L3000 1PZ UNIONE W.G.ALTO	1086A2.99
	HERO: STAFFA PARETE "L" CAP	108687.21