



## Features

Use: Indoor  
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK  
Emission: DIRECT  
Optics: OPAL  
Colour: BLACK  
Dimming: PUSH, DALI  
Emergency: Autonomy 1h/Recharge time 12h  
L: 1680mm  
A: 53mm  
H: 69mm  
Made in: ITALY  
Warranty: 5 years except battery

## Tech data

Luminaire input power: 40.5W  
Luminaire luminous flux: 3220lm  
Luminous flux in emergency: 10%  
IP: 40  
Insulation class: I  
No. of driver per product: 1  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

## Source

Light source: LED  
Source power: 36W  
Colour temperature: 4000K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012, CEI EN 60598-2-22:2023

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

# HERO

108698.02 + 108903.99

HERO: EM 36W 4K 1680 DALI NE + HERO: DIFF. OPALE PER 1680



**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



## Features

Use: Indoor  
Optics: OPAL  
L: 1680mm  
A: 48mm  
H: 6mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 0.4kg

## Tech data

IP: 40



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 14/11/2024, 18:53:04

COMPLETION ACCESSORIES

|                                                                                     |                               |           |
|-------------------------------------------------------------------------------------|-------------------------------|-----------|
|    | HERO: MOD.CIECO 250 NE        | 108676.02 |
|    | HERO: MOD.CIECO ANG.DX 150 NE | 108678.02 |
|    | HERO: COPPIA TESTATE NE       | 108684.02 |
|    | HERO: MOD.CIECO ANG.SX 150 NE | 108677.02 |
|   | HERO: MOD.CIECO 1680 NE       | 108681.02 |
|  | HERO: MOD.CIECO 1120 NE       | 108679.02 |
|  | HERO: MOD.CIECO 1400 NE       | 108680.02 |

MOUNTING ACCESSORIES

|                                                                                                  |                                 |           |
|--------------------------------------------------------------------------------------------------|---------------------------------|-----------|
|  | HERO: STAFFA PARETE "L" NE      | 108687.02 |
|               | HERO: SOSPL3000 1PZ. TESTA/CODA | 108685.99 |
|               | KIT ALIMENTAZIONE L3000 5P NE   | 108922.02 |
|               | HERO: SPESS. CARTONG. 10MM 2PZ. | 108689.99 |



HERO: SOSP.L3000 1PZ. UNIONE

**108686.99**



HERO: SOSP.L3000 1PZ TESTA W.G.ALTO

**1086A1.99**



HERO: KIT INCASSO LED (1X)

**108688.99**



KIT ALIMENTAZIONE L1200 5P NE

**108921.02**



HERO: SOSP.L3000 1PZ UNIONE W.G.ALTO

**1086A2.99**