



Features

Use: Indoor
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK
Emission: DIRECT
Beam: 36°
Colour: CAFFE
Dimming: PUSH, DALI
Emergency: Autonomy 3h/Recharge time 24h
L: 250mm
A: 53mm
H: 69mm
Made in: ITALY
Warranty: 5 years except battery

Tech data

Luminaire input power: 5W
Luminaire luminous flux: 140lm
Luminous flux in emergency: 100%
IP: 40
Insulation class: I
Supply voltage: 220-240V 50/60Hz
SELV: No

Source

Light source: LED
Source power: 1W
Colour temperature: 4500K
CRI: >80

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012, CEI EN 60598-2-22:2023

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)

COMPLETION ACCESSORIES

	HERO: COPPIA TESTATE CAF	108684.20
---	--------------------------	-----------