

## Features

Use: Indoor  
Type of installation: RECESSED INTO PLASTERBOARD  
Emission: DIRECT  
Optics: MICRO OPTICS  
Colour: BLACK  
Dimming: PUSH, DALI  
Emergency: NO  
L: 868mm  
A: 61mm  
H: 68mm  
Made in: ITALY  
Warranty: 5 years

## Tech data

Luminaire input power: 26.5W  
Luminaire luminous flux: 2134lm  
IP: 40  
Insulation class: I  
No. of driver per product: 1  
Supply voltage: 220-240V 50/60Hz  
UGR: <19  
SELV: Si

## Source

Light source: LED  
Source power: 22W  
Colour temperature: 2700K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

## Standards








Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

## Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

[View more product info](#)

COMPLETION ACCESSORIES

|                                                                                    |                                 |           |
|------------------------------------------------------------------------------------|---------------------------------|-----------|
|    | HERO C: MOD.CIECO 250 NE        | 108852.02 |
|    | HERO C: MOD.CIECO ANG.SX 150 NE | 108853.02 |
|    | HERO C: MOD.CIECO ANG.DX 150 NE | 108854.02 |
|    | HERO C: MOD.CIECO 1120 NE       | 108855.02 |
|   | HERO C: MOD.CIECO 1400 NE       | 108856.02 |
|  | HERO C: MOD.CIECO 1680 NE       | 108857.02 |
|  | HERO C: COPPIA TESTATE NE       | 108860.02 |