



Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: SPOT
Beam: 14°
Colour: WHITE
Dimming: PUSH, DALI
Emergency: NO
L: 1120mm
A: 61mm
H: 68mm
Made in: ITALY
Warranty: 5 years
Weight: 3.4kg

Tech data

Luminaire input power: 29W
Luminaire luminous flux: 2028lm
IP: 40
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 2x13W
Source luminous flux: 2644lm
Colour temperature: 2700K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



COMPLETION ACCESSORIES

	HERO C: MOD.CIECO 250 BIA	108852.01
	HERO C: MOD.CIECO ANG.DX 150 BIA	108854.01
	HERO C: MOD.CIECO 1120 BIA	108855.01
	HERO C: MOD.CIECO 1400 BIA	108856.01
	HERO C: MOD.CIECO 1680 BIA	108857.01
	HERO C: COPPIA TESTATE BIA	108860.01