



Features

Use: Indoor
Type of installation: SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL
Colour: CAFFE
Dimming: WITH ACCESSORY
Emergency: NO
L: Ø 962mm
A: 40mm
H: 40mm
Made in: ITALY
Warranty: 5 years
Weight: 6.5kg

Tech data

Luminaire input power: 66.1W
Luminaire luminous flux: 3947lm
IP: 40
Insulation class: III
Supply voltage: MAX 1.8A
UGR: <19
SELV: No

Source

Light source: LED
Source power: 62W
Source luminous flux: 8502lm
Colour temperature: 2700K
CRI: >90
LED lifespan: 50000h

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

COMPLETION ACCESSORIES

	ARK/HALOS: KIT GIUNZIONE PROFILI NE	109809.02
---	-------------------------------------	-----------

MOUNTING ACCESSORIES

	CAVO ALIMENTAZIONE L=3000 3X1.5 TRASP	109001.00
---	---------------------------------------	-----------

	HALOS: KIT 4 CAVI SOSPENSIONE L.3000	105159.99
---	--------------------------------------	-----------

	HALOS: ROSONE ALIM. REMOTA CAFFE	105157.20
---	----------------------------------	-----------

	HALOS: ROSONE DOPPIA ALIM. REMOTA CAFFE	105158.20
---	---	-----------

ELECTRICAL ACCESSORIES

	HALOS: ROSONE ALIM. ON/OFF CAFFE	105149.20
---	----------------------------------	-----------

	HALOS: ROSONE-N DOPPIA ALIM ON/OFF CAFFE	105155.20
---	--	-----------

	HALOS: ROSONE-N ALIM. ON/OFF CAFFE	105151.20
---	------------------------------------	-----------

	HALOS: ALIMENTATORE ON/OFF	105147.99
---	----------------------------	-----------

HALOS ACOUSTIC

109901.20

DIMMABLE ACCESSORIES

	HALOS: ROSONE ALIM. DALI/PUSH CAFFE	105150.20
	HALOS: ALIMENTATORE DALI/PUSH	105148.99
	HALOS: ROSONE-N ALIM. DALI/PUSH CAFFE	105152.20
	HALOS: ROSONE-N DOPPIA ALIM D/PUSH CAFFE	105156.20

