

Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: OPAL
Beam: 100°
Colour: WHITE
Dimming: WITH ACCESSORY
Emergency: WITH ACCESSORY
H: 28mm
ø: Ø230
D: 210-215mm
Warranty: 5 years
Weight: 0.73kg

Tech data

Luminaire input power: 23W
Luminaire luminous flux: 1950lm
Luminous flux in emergency: 1h: 22% / 3h: 9%
IP: 40
Insulation class: II
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 20W
Source luminous flux: 2300lm
Colour temperature: 3000K
CRI: >90
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

COMPLETION ACCESSORIES



SLIM: ADATT.PER FORO 240MM / 250MM

11814.01


DIMMABLE ACCESSORIES



ALIM. LED 25W 350MA/2-50V DALI/PUSH


101333.99

EMERGENCY ACCESSORIES



KIT EMERGENZA 3H 10V-54V

18005.99



KIT EMERGENZA 1H 10V-54V

18004.99