



Features

Use: Indoor
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK
Emission: DIRECT
Optics: OPAL FULL LIGHT
Colour: WHITE
Dimming: PUSH, DALI
Emergency: Autonomy 1h/Recharge time 12h
L: 1680mm
A: 53mm
H: 69mm
Made in: ITALY
Warranty: 5 years except battery
Weight: 5.2kg

Tech data

Luminaire input power: 55W
Luminaire luminous flux: 4100lm
Luminous flux in emergency: 10%
IP: 40
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 49W
Colour temperature: 2700K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012, CEI EN 60598-2-22:2023

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)



Features

Use: Indoor
Optics: OPAL FULL LIGHT
L: 1680mm
A: 52.5mm
H: 15mm
Made in: ITALY
Warranty: 5 years
Weight: 0.13kg

Tech data


IP: 40



COMPLETION ACCESSORIES

	HERO: MOD.CIECO 250 BIA	108676.01
	HERO: MOD.CIECO ANG.SX 150 BIA	108677.01
	HERO: MOD.CIECO ANG.DX 150 BIA	108678.01
	HERO: MOD.CIECO 1120 BIA	108679.01
	HERO: MOD.CIECO 1400 BIA	108680.01
	HERO: MOD.CIECO 1680 BIA	108681.01
	HERO: COPPIA TESTATE BIA	108684.01

MOUNTING ACCESSORIES

	HERO: SOSPL3000 1PZ TESTA W.G.ALTO	1086A1.99
	HERO: SOSPL3000 1PZ UNIONE W.G.ALTO	1086A2.99
	HERO: SOSPL3000 1PZ. TESTA/CODA	108685.99
	HERO: SOSPL3000 1PZ. UNIONE	108686.99



HERO: STAFFA PARETE "L" BIA

108687.01



HERO: KIT INCASSO LED (1X)

108688.99



HERO: SPESS. CARTONG. 10MM 2PZ.

108689.99



KIT ALIMENTAZIONE L1200 5P BIA

108921.01



KIT ALIMENTAZIONE L3000 5P BIA

108922.01