

Features

Use: Indoor
Dimming: WITH ACCESSORY
Emergency: NO
L: 249mm
ø: 300mm
Made in: ITALY
Warranty: 5 years
Weight: 0.03kg

Tech data

Luminaire luminouse flux: 435lm
IP: 20
Insulation class: III
Supply voltage: 48 Vdc

Source

Light source: LED
Source power: 3,3W
Colour temperature: 2700K
CRI: >90
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)





DOMYNOS PS

112212.99

MOUNTING ACCESSORIES

	DOMYNOS PS: CAVO DI SOSPENSIONE	112229.99
---	---------------------------------	-----------

ELECTRICAL ACCESSORIES

	DOMYNOS PS: ROSONE SOSP. 100W-48V BIA	112230.01
	DOMYNOS PS: ROSONE SOSP. 100W-48V NE	112230.02
	DOMYNOS PS: ROSONE SOSP. 100W-48V CAF	112230.20
	DOMYNOS PS: ROSONE SOSP. 100W-48V CAPP	112230.21
	DOMYNOS PS: ROSONE SOSP DALI 150W-48V BI	112232.01
	DOMYNOS PS: ROSONE SOSP DALI 150W-48V NE	112232.02
	DOMYNOS PS: ROSONE SOSP DALI 150W-48V CF	112232.20
	DOMYNOS PS: ROSONE SOSP DALI 150W-48V CP	112232.21
	ALIMENTATORE 48V 320W IP65	101313.99
	ALIMENTATORE 48V 100W IP65	101314.99



DOMYNOS PS

112212.99

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



ALIMENTATORE 48V 150W IP65

101337.99

DIMMABLE ACCESSORIES



INTERF.DIMM.12-48V DALI/1-10V/0-10V/PUSH

105914.99



INTERF.DIMM.12-48V LC

105923.99



Novalux S.r.l. via Marzabotto, 2 40050 Fano di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 14/11/2024, 18:20:56