HERO MINI SYSTEM

113225.21



Features

Use: Indoor
Optics: SPOT
Beam: 25°
Colour: CAPPUCCINO
Dimming: WITH ACCESSORY
Emergency: NO
L: 636mm
A: 32mm
H: 12mm
Made in: ITALY
Warranty: 5 years

Tech data

Luminaire input power: 13W
Luminaire luminouse flux: 771lm
IP: 40
Insulation class: III
Supply voltage: DC 700 MA

Source

Light source: LED
Source power: 2X4W
Colour temperature: 4000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 1Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

View more product info

Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV Gmbh

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 14/11/2024, 18:22:34