

Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: MICROPRISMATIZED
Colour: WHITE
Dimming: PUSH, DALI
Emergency: WITH ACCESSORY
L: 1195mm
A: 295mm
H: 35mm
Warranty: 3 years
Weight: 3.2kg

Tech data

Luminaire input power: 36W
Luminaire luminous flux: 4080lm
Luminous flux in emergency: 1h: 12% / 3h: 5
IP: 40
Insulation class: II
No. of driver per product: 1
Supply voltage: 900mA driver incluso
UGR: <19 4H-8H S=0,25
SELV: Si

Source

Light source: LED
Source power: 32W
Source luminous flux: 5149lm
Colour temperature: 4000K
CRI: >80
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012


Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.


[View more product info](#)


MOUNTING ACCESSORIES

	BACKLIT: KIT MOLLE INC.CART.600/1200	113609.99
---	--------------------------------------	-----------

	BACKLIT: BOX PER INST. PLAF. 1200X300 BI	113611.01
--	--	-----------

EMERGENCY ACCESSORIES

	THE PANEL 2: EMER.INC.3H 10/54VDC	1020A5.99
--	-----------------------------------	-----------

	THE PANEL 2: EMER.INC.1H 10/54VDC	1020A4.99
--	-----------------------------------	-----------