

STRIP LED

100985.99

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor, Outdoor
Dimming: WITH ACCESSORY
Emergency: WITH ACCESSORY
L: 5000mm
A: 10mm
Warranty: 5 years
Weight: 0.15kg

Tech data

Luminaire luminouse flux: 812lm
Luminous flux in emergency: L min = 30 L max = 130 - 1h: 17% / 3h: 7
IP: 65
Insulation class: III
Supply voltage: 24 Vdc
SELV: Sì

Source

Light source: LED
Source power: 8.8W/m
Source luminous flux: 812lm
Colour temperature: 4000K
CRI: >90
LED lifespan: 30000h L70 B20


Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[STRIP LED: View more product info](#)



SMD 3528 (240 LED/m)
Biadesivo - sezionabile ogni 25mm (6 LED)
Biadesive - cuttable every 25mm (6 LED)





Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 19/5/2025, 12:30:54

STRIP LED

100985.99

EMERGENCY ACCESSORIES

	KIT EMERGENZA 1H 10V-54V	18004.99
	KIT EMERGENZA 3H 10V-54V	18005.99