

Features

Use: Indoor
Dimming: WITH ACCESSORY
Emergency: WITH ACCESSORY
L: 2040mm
A: 15mm
H: 12mm
Warranty: 5 years

Tech data

Luminaire luminous flux: 952lm
Luminous flux in emergency: L min = 50 L max = 200 - 1h: 17% / 3h: 7
IP: 65
Insulation class: III
Supply voltage: 24 Vdc
SELV: Sì

Source

Light source: LED
Source power: 12W/m
Source luminous flux: 1840lm
Colour temperature: 3000K
CRI: >80
LED lifespan: 30000h L70 B20

Compliance


CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 1
Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[STRIP LED: View more product info](#)

[PROFILED FLEX: View more product info](#)



STRIP LED | PROFILED FLEX

1009A2.99

novalux
ITALIAN LIGHTING DESIGN SINCE 1948


COMPLETION ACCESSORIES



STRIP LED 230VAC: SIGILLANTE


100966.99

EMERGENCY ACCESSORIES



KIT EMERGENZA 1H 10V-54V


18004.99



KIT EMERGENZA 3H 10V-54V

18005.99

PRODUCTS



PROFILED: PROF. FLEX ALLUMINIO 2M

105427.96



Novalux S.r.l. via Marzabotto, 2 40050 Fano di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 19/5/2025, 12:30:55