

Features

Use: Indoor
Dimming: WITH ACCESSORY
Emergency: WITH ACCESSORY
L: 2040mm
A: 15mm
H: 12mm
Warranty: 5 years

Tech data

Luminaire luminous flux: 991lm
Luminous flux in emergency: L min = 50 L max = 200 - 1h: 17% / 3h: 7
IP: 65
Insulation class: III
Supply voltage: 24 Vdc
SELV: Sì

Source

Light source: LED
Source power: 12 W/m
Source luminous flux: 1903lm
Colour temperature: 4000K
CRI: >80
LED lifespan: 30000h L70 B20

Compliance


CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 1
Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[STRIP LED: View more product info](#)

[PROFILED FLEX: View more product info](#)




STRIP LED | PROFILED FLEX


1009A3.99

COMPLETION ACCESSORIES

	STRIP LED 230VAC: SIGILLANTE	100966.99
---	------------------------------	-----------

EMERGENCY ACCESSORIES

	KIT EMERGENZA 1H 10V-54V	18004.99
--	--------------------------	----------

	KIT EMERGENZA 3H 10V-54V	18005.99
--	--------------------------	----------

PRODUCTS

	PROFILED: PROF. FLEX ALLUMINIO 2M	105427.96
--	-----------------------------------	-----------

