



## Features

Use: Indoor  
Type of installation: WALL, SUSPENDED, CEILING MOUNTED  
Emission: DIRECT  
Optics: MICRO OPTICS  
Colour: WHITE  
Dimming: ON/OFF  
Emergency: NO  
L: 1314mm  
A: 1138mm  
H: 60mm  
Made in: ITALY  
Warranty: 5 years

## Tech data

Luminaire input power: 30W  
Luminaire luminous flux: 2840lm  
IP: 40  
Insulation class: I  
No. of driver per product: 2  
Supply voltage: 220-240V 50/60Hz  
UGR: <19  
SELV: Si

## Source

Light source: LED  
Source power: 26W  
Source luminous flux: 3360lm  
Colour temperature: 4000K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[SIX ACOUSTIC: View more product info](#)

[SIX: View more product info](#)



## MOUNTING ACCESSORIES

	ROSONE 3X1,5 TND 3000 BIA	<b>109005.01</b>
	ROSONE 3X1,5 QDR 3000 BIA	<b>109006.01</b>
	ROSONE 5X1,5 TND 3000 BIA	<b>109007.01</b>
	ROSONE 5X1,5 QDR 3000 BIA	<b>109008.01</b>
	SIX: KIT SOSPENSIONE 6 PZ	<b>113713.99</b>