



Features

Use: Indoor
Type of installation: WALL, SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: MICRO OPTICS
Colour: WHITE
Dimming: PUSH, DALI
Emergency: NO
L: 1314mm
A: 1138mm
H: 60mm
Made in: ITALY
Warranty: 5 years

Tech data

Luminaire input power: 30W
Luminaire luminous flux: 2840lm
IP: 40
Insulation class: I
No. of driver per product: 2
Supply voltage: 220-240V 50/60Hz
UGR: <19
SELV: Si

Source

Light source: LED
Source power: 26W
Source luminous flux: 3360lm
Colour temperature: 4000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[SIX ACOUSTIC: View more product info](#)

[SIX: View more product info](#)



MOUNTING ACCESSORIES

	ROSONE 3X1,5 TND 3000 BIA	109005.01
	ROSONE 3X1,5 QDR 3000 BIA	109006.01
	ROSONE 5X1,5 TND 3000 BIA	109007.01
	ROSONE 5X1,5 QDR 3000 BIA	109008.01
	SIX: KIT SOSPENSIONE 6 PZ	113713.99