



## Driver DALI™

### DALI PUSH DIM DRIVER (MAX 42W) FOR DL151065, LP149512 & LP149505 & LP154288 & LP155803

- Le driver DR159429 est un driver gradable DALI-2 et PushDIM à courant constant réglable. Il est livré équipé de son cordon de raccordement au luminaire.
- Plage de gradation de 1 à 100%.
- Absence de scintillement et gradation douce quelle que soit la luminosité.
- Réglage du courant de sortie ( 10 niveaux ) à l'aide de micro-interrupteurs.
- Compatible CBS ( Central Battery System ) pour l'éclairage de secours.
- Serre-câbles indépendants ( entrée / sortie ).

| Code            | Puissance | Variation         | Tension d'alimentation & Fréquence | Tension de sortie | Courant de sortie    | Classe électrique |
|-----------------|-----------|-------------------|------------------------------------|-------------------|----------------------|-------------------|
| <b>DR159429</b> | 16 - 42W  | DALI-2 / PUSH DIM | 200 - 240 VAC/VDC<br>50/60Hz       | 6 - 42 VDC        | 450 - 1100mA<br>Maxi | SELV Class II     |



01/08/2025

Warranties may be available on certain products as indicated in the product description and are valid from the date of purchase. The warranty is invalid in the case of improper use, installation in an unsuitable working environment, tampering or removal of the Quality Control date label. In the event of product failure during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. SWITCH LITE does not accept responsibility for any installation costs associated with the replacement of this product and reserves the right to alter specifications without prior notice.

## Driver DALI™

DALI PUSH DIM DRIVER (MAX 42W) FOR DL151065, LP149512 & LP149505 & LP154288 & LP155803

| Features                            |                   |
|-------------------------------------|-------------------|
| Tension d'alimentation              | 200 - 240 VAC/VDC |
| Tension de sortie                   | 6 - 42 VDC        |
| Courant de sortie                   | 450 - 1100mA Maxi |
| Puissance                           | 16 - 42W          |
| Classe Electrique                   | SELV Class II     |
| Variation                           | DALI-2 / PUSH DIM |
| Indice de protection                | IP20              |
| Température ambiante                | -20°C / 45°C      |
| TC Maxi                             | 90°C              |
| Facteur de puissance (PF)           | >0.97             |
| Taux de distorsion harmonique (THD) | <5%               |

| Logistic            |               |
|---------------------|---------------|
| Hauteur du produit  | 40 mm         |
| Largeur du produit  | 76 mm         |
| Longueur du produit | 121 mm        |
| Poids Net           | 173 g         |
| EAN / Code Barre    | 3609640159429 |

01/08/2025