



**Electrical features**

Maximum operating current ( $\leq 440V$ ) A 12

**Contact characteristics**

Operational current Ie AC-3 ( $\leq 440V \leq 55^{\circ}C$ ) A 12

Rated operational power AC-3 ( $T \leq 55^{\circ}C$ )	V	kW	
	230V	kW	3.2
	400V	kW	5.7
	415V	kW	6.2
	440V	kW	5.5
	500V	kW	5
	690V	kW	5

Built-in auxiliary contacts

	NO	0
	NC	1

**UL technical data**

Maximum UL/CSA horsepower ratings single-phase

	110V-120V	HP	0.5
	220V-240V	HP	1.5

Maximum UL/CSA horsepower ratings three-phase, 3-pole


	200V-208V	HP	3
	220V-240V	HP	3
	440V-480V	HP	7.5
	550V-600V	HP	10

**Mechanical features**

Terminals type Clamp screw

Weight g 394

**Dimensions**



Wiring diagrams



Certifications and compliance

Compliance

IEC/EN 60947-1  
IEC/EN 60947-4-1  
UL508 CSA C22.2 n° 14

Certificates

cULus

ETIM classification

ETIM 8.0

EC001037 -  
Motor  
starter/Motor  
starter  
combination