

Product designation


## SOUND-LIGHT PULSED OR CONTINUOUS MODULE. Ø62MM. BULB INCLUDED, ORANGE, 24VAC/DC (80DB)




Signal beacons Ø62mm/2.44"


| Product type designation            |     |          | 8LB6S                 |
|-------------------------------------|-----|----------|-----------------------|
| General characteristics             |     |          |                       |
| Diameter                            | m   | m - inch | 62 / 2.44             |
| Supply voltage (AC)                 |     | V        | 24                    |
| Supply voltage (DC)                 |     | V        | 24                    |
| Colour                              |     |          | Orange                |
| IEC degree of protection            |     |          | IP54                  |
| Sound module consumption (AC)       |     | mΑ       | 150                   |
| Sound module consumption (DC)       |     | mΑ       | 150                   |
| Sound intensity                     |     | dB       | 80                    |
| Mechanical features                 |     |          |                       |
| Tightening torque for terminals max |     | Nm       | 0.5                   |
| Terminals screw                     |     |          | Screw clamp terminals |
| Conductor section                   |     |          |                       |
| AWG/Kcmil                           |     |          |                       |
|                                     | max |          | 16                    |
| IEC                                 |     |          |                       |
|                                     | max | mm²      | 1.5                   |
| Weight                              |     | g        | 60                    |
| Ambient conditions                  |     |          |                       |
| Temperature                         |     |          |                       |
| Operating temperature               |     |          |                       |
|                                     | min | °C       | -20                   |
|                                     | max | °C       | +50                   |

**Dimensions** 





## Wiring diagrams



## Certifications and compliance

Compliance

IEC/EN 60947-1

IEC/EN 60947-5-1

Certificates

EAC

ETIM classification

ETIM 8.0

EC000232 -Optical module for signal tower