



### Contact characteristics

|   |                    |        |
|---|--------------------|--------|
| Number of poles   | Nr.                | 3      |
| Rated insulation voltage U <sub>i</sub> IEC/EN                              | V                  | 690    |
| Rated impulse withstand voltage U <sub>imp</sub>                            | kV                 | 6      |
| Operational frequency   | min                | Hz 25  |
|   | max                | Hz 400 |
| IEC Conventional free air thermal current I <sub>th</sub> ≤ 40°C            | A                  | 32     |
| Operational current I <sub>e</sub>  | AC-1 (≤40°C)       | A 32   |
|   | AC-1 (≤55°C)       | A 26   |
|   | AC-1 (≤70°C)       | A 23   |
|   | AC-3 (≤440V ≤55°C) | A 18   |
|   | AC-4 (400V)        | A 8.5  |
| Rated operational power AC-3 (T≤55°C)                                       | 230V               | kW 4   |
|   | 400V               | kW 7.5 |
|   | 415V               | kW 9   |
|   | 440V               | kW 9   |
|   | 500V               | kW 10  |
|   | 690V               | kW 10  |
| Rated operational power AC-1 (T≤40°C)                                       | 230V               | kW 12  |
|   | 400V               | kW 21  |
|   | 500V               | kW 26  |
|   | 690V               | kW 36  |
| IEC max current I <sub>e</sub> in DC1 with L/R ≤ 1ms with 1 poles in series | ≤24V               | A 17   |
|   | 48V                | A 15   |
|   | 75V                | A 15   |
|   | 110V               | A 6    |
|   | 220V               | A –    |
| IEC max current I <sub>e</sub> in DC1 with L/R ≤ 1ms with 2 poles in series | ≤24V               | A 20   |
|   | 48V                | A 20   |
|   | 75V                | A 20   |
|   | 110V               | A 13   |
|   | 220V               | A 1    |
| IEC max current I <sub>e</sub> in DC1 with L/R ≤ 1ms with 3 poles in series | ≤24V               | A 22   |
|   | 48V                | A 22   |
|   | 75V                | A 20   |
|   | 110V               | A 16   |
|   | 220V               | A 11   |
| IEC max current I <sub>e</sub> in DC1 with L/R ≤ 1ms with 4 poles in series |                    |        |

|  |                 |                  |      |
|--|-----------------|------------------|------|
|  | ≤24V            | A                | 22   |
|  | 48V             | A                | 22   |
|  | 75V             | A                | 20   |
|  | 110V            | A                | 18   |
|  | 220V            | A                | 13   |
| <hr/>  |                 |                  |      |
| IEC max current I <sub>e</sub> in DC3-DC5 with L/R ≤ 15ms with 1 poles in series | ≤24V            | A                | 12   |
|  | 48V             | A                | 11   |
|  | 75V             | A                | 11   |
|  | 110V            | A                | 2    |
|  | 220V            | A                | –    |
| <hr/>  |                 |                  |      |
| IEC max current I <sub>e</sub> in DC3-DC5 with L/R ≤ 15ms with 2 poles in series | ≤24V            | A                | 15   |
|  | 48V             | A                | 13   |
|  | 75V             | A                | 13   |
|  | 110V            | A                | 8    |
|  | 220V            | A                | 2    |
| <hr/>  |                 |                  |      |
| IEC max current I <sub>e</sub> in DC3-DC5 with L/R ≤ 15ms with 3 poles in series | ≤24V            | A                | 18   |
|  | 48V             | A                | 18   |
|  | 75V             | A                | 16   |
|  | 110V            | A                | 12   |
|  | 220V            | A                | 6    |
| <hr/>  |                 |                  |      |
| IEC max current I <sub>e</sub> in DC3-DC5 with L/R ≤ 15ms with 4 poles in series | ≤24V            | A                | 18   |
|  | 48V             | A                | 18   |
|  | 75V             | A                | 16   |
|  | 110V            | A                | 13   |
|  | 220V            | A                | 8    |
| <hr/>  |                 |                  |      |
| Short-time allowable current for 10s (IEC/EN60947-1)                             |                 | A                | 200  |
| <hr/>  |                 |                  |      |
| Protection fuse  | gG (IEC)        | A                | 32   |
|  | aM (IEC)        | A                | 20   |
| <hr/>  |                 |                  |      |
| Making capacity (RMS value)  |                 | A                | 180  |
| <hr/>  |                 |                  |      |
| Breaking capacity at voltage   | 440V            | A                | 144  |
|  | 500V            | A                | 120  |
|  | 690V            | A                | 94   |
| <hr/>  |                 |                  |      |
| Resistance per pole (average value)  |                 | mΩ               | 2.5  |
| <hr/>  |                 |                  |      |
| Power dissipation per pole (average value)                                       | I <sub>th</sub> | W                | 2.6  |
|  | AC-3            | W                | 0.8  |
| <hr/>  |                 |                  |      |
| Tightening torque for terminals  | min             | Nm               | 1.5  |
|  | max             | Nm               | 1.8  |
|  | min             | I <sub>bin</sub> | 1.1  |
|  | max             | I <sub>bin</sub> | 1.5  |
| <hr/>  |                 |                  |      |
| Tightening torque for coil terminal  | min             | Nm               | 0.8  |
|  | max             | Nm               | 1    |
|  | min             | I <sub>bin</sub> | 0.8  |
|  | max             | I <sub>bin</sub> | 0.74 |
| <hr/>  |                 |                  |      |
| Max number of wires simultaneously connectable                                   |                 | Nr.              | 2    |

Conductor section

|   |     |                 |     |    |
|---|-----|-----------------|-----|----|
| AWG/Kcmil   |     |                 | max | 10 |
| Flexible w/o lug conductor section                  | min | mm <sup>2</sup> | 1   |    |
|   | max | mm <sup>2</sup> | 6   |    |
| Flexible c/w lug conductor section                  | min | mm <sup>2</sup> | 1   |    |
|   | max | mm <sup>2</sup> | 4   |    |
| Flexible with insulated spade lug conductor section | min | mm <sup>2</sup> | 1   |    |
|   | max | mm <sup>2</sup> | 4   |    |

Power terminal protection according to IEC/EN 60529

IP20 when properly wired

Cable stripping length

|                 |    |    |
|-----------------|----|----|
| main circuit    | mm | 10 |
| command circuit | mm | 8  |

Mechanical features

Operating position

|                  |                    |
|------------------|--------------------|
| normal allowable | Vertical plan ±30° |
|------------------|--------------------|

Fixing

Screw / DIN rail 35mm

Weight

g 358

Auxiliary contact characteristics

Thermal current I<sub>th</sub>

A 10

IEC/EN 60947-5-1 designation

A600 - P600

Operating current AC15

|      |   |     |
|------|---|-----|
| 230V | A | 3   |
| 400V | A | 1.9 |
| 500V | A | 1.4 |

Operating current DC12

|      |   |     |
|------|---|-----|
| 110V | A | 5.7 |
|------|---|-----|

Operating current DC13

|      |   |      |
|------|---|------|
| 24V  | A | 5.7  |
| 48V  | A | 2.9  |
| 60V  | A | 2.3  |
| 110V | A | 1.25 |
| 125V | A | 1.1  |
| 220V | A | 0.55 |
| 600V | A | 0.2  |

Operations

Mechanical life

cycles 20000000

Electrical life

cycles 1600000

Safety related data

Performance level B10d according to EN/ISO 13489-1

|                 |        |          |
|-----------------|--------|----------|
| rated load      | cycles | 1600000  |
| mechanical load | cycles | 20000000 |

EMC compatibility

yes

AC coil operating

Rated AC voltage at 50/60Hz

V 230

AC operating voltage

of 50/60Hz coil powered at 50Hz

|  |          |          |      |
|--|----------|----------|------|
| pick-up  | min      | %Us      | 80   |
|  | max      | %Us      | 110  |
| drop-out   | min      | %Us      | 20   |
|  | max      | %Us      | 55   |
| of 50/60Hz coil powered at 60Hz                  |          |          |      |
| pick-up  | min      | %Us      | 85   |
|  | max      | %Us      | 110  |
| drop-out   | min      | %Us      | 20   |
|  | max      | %Us      | 55   |
| AC average coil consumption at 20°C              |          |          |      |
| of 50/60Hz coil powered at 50Hz                  |          |          |      |
|  | in-rush  | VA       | 75   |
|  | holding  | VA       | 9    |
| of 50/60Hz coil powered at 60Hz                  |          |          |      |
|  | in-rush  | VA       | 70   |
|  | holding  | VA       | 6.5  |
| of 60Hz coil powered at 60Hz                     |          |          |      |
|  | in-rush  | VA       | 75   |
|  | holding  | VA       | 9    |
| Dissipation at holding ≤20°C 50Hz                |          | W        | 2.5  |
| <b>Max cycles frequency</b>                      |          |          |      |
| Mechanical operation                             |          | cycles/h | 3600 |
| <b>Operating times</b>                           |          |          |      |
| Average time for U <sub>s</sub> control          |          |          |      |
| in AC  |          |          |      |
| Closing NO                                       | min      | ms       | 8    |
|  | max      | ms       | 24   |
| Opening NO                                       | min      | ms       | 10   |
|  | max      | ms       | 20   |
| Closing NC                                       | min      | ms       | 14   |
|  | max      | ms       | 28   |
| Opening NC                                       | min      | ms       | 7    |
|  | max      | ms       | 18   |
| <b>UL technical data</b>                         |          |          |      |
| Rated operational voltage AC (UL)                |          | V        | 600  |
| Full-load current (FLA) for three-phase AC motor |          |          |      |
|  | at 480V  | A        | 14   |
|  | at 600V  | A        | 17   |
| Yielded mechanical performance                   |          |          |      |
| for single-phase AC motor                        |          |          |      |
|  | 110/120V | HP       | 1    |
|  | 230V     | HP       | 3    |
| for three-phase AC motor                         |          |          |      |
|  | 200/208V | HP       | 5    |
|  | 220/240V | HP       | 5    |
|  | 460/480V | HP       | 10   |

|   |                       |                       |    |             |
|---|-----------------------|-----------------------|----|-------------|
|   |                       | 575/600V              | HP | 15          |
| <b>General USE</b>  |                       |                       |    |             |
|   | Contactor             | AC current            | A  | 32          |
|   | Auxiliary contacts    | AC voltage            | V  | 600         |
|   |                       | AC current            | A  | 10          |
|   |                       | DC voltage            | V  | 250         |
|   |                       | DC current            | A  | 1           |
| <b>Short-circuit protection fuse, 600V</b>                  |                       |                       |    |             |
|   | High fault            | Short circuit current | kA | 100         |
|   |                       | Fuse rating           | A  | 60          |
|   |                       | Fuse class            |    | J           |
|   | Standard fault        | Short circuit current | kA | 5           |
|   |                       | Fuse rating           | A  | 80          |
| <b>Contact rating of auxiliary contacts according to UL</b> |                       |                       |    | A600 - P600 |
| <b>Ambient conditions</b>                                   |                       |                       |    |             |
| <b>Temperature</b>  |                       |                       |    |             |
|   | Operating temperature | min                   | °C | -50         |
|   |                       | max                   | °C | 70          |
|   | Storage temperature   | min                   | °C | -60         |
|   |                       | max                   | °C | 80          |
| <b>Max altitude</b>   |                       |                       | m  | 3000        |
| <b>Resistance &amp; Protection</b>                          |                       |                       |    |             |
| <b>Pollution degree</b>                                     |                       |                       |    | 3           |
| <b>Dimensions</b>   |                       |                       |    |             |



**Wiring diagrams**



**Certifications and compliance**

Compliance

- CSA C22.2 n° 60947-1
- CSA C22.2 n° 60947-4-1
- IEC/EN 60335-2-89
- IEC/EN/BS 60947-1
- IEC/EN/BS 60947-4-1
- UL 60947-1
- UL 60947-4-1

Certificates

CCC

CSA C22.2 n. 60335-2-40:22 LZGH A2L

CSA C22.2 No. 60335-2-89:21 LZGH A2L

cULus

EAC

UL 60335-2-40 LZGH A2L

UL 60335-2-89 LZGH A2L

ETIM classification

ETIM 8.0

EC000066 -  
Power contactor,  
AC switching