



Electrical features

Maximum operating current ($\leq 440V$)	A	12
---	---	----

Contact characteristics

Operational current I_e	AC-3 ($\leq 440V \leq 55^\circ C$)	A	12
---------------------------	--------------------------------------	---	----

Rated operational power AC-3 ($T \leq 55^\circ C$)	230V	kW	3.2
	400V	kW	5.7
	415V	kW	6.2
	440V	kW	6.2
	500V	kW	7.5
	690V	kW	10

Built-in auxiliary contacts	NO	0
	NC	1

UL technical data

Maximum UL/CSA horsepower ratings single-phase	110V-120V	HP	1
	220V-240V	HP	2


Maximum UL/CSA horsepower ratings three-phase, 3-pole	200V-208V	HP	5
	220V-240V	HP	5
	440V-480V	HP	7.5
	550V-600V	HP	10

Mechanical features


Terminals type	Clamp screw
----------------	-------------

Weight	g	760
--------	---	-----

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

IEC/EN 60947-1
IEC/EN 60947-4-1
UL508 CSA C22.2 n° 14

Certificates

cULus

ETIM classification

ETIM 8.0

EC001037 -
Motor
starter/Motor
starter
combination