



Auxiliary supply Us			
Auxiliary rated supply voltage AC	VAC		100...240
Auxiliary rated supply voltage DC	VDC		110...250
Auxiliary operating voltage range			
AC			
	min	VAC	85
	Max	VAC	264
DC			
	min	VDC	93.5
	Max	VDC	300
Operational frequency			
	min	Hz	50
	max	Hz	60
Power consumption			
	Max	VA	3.5
Power dissipation Max		W	1.2
Measuring voltage inputs			
Rated voltage (Ue)			
	phase-phase	VAC	690
	phase-neutral	VAC	400
Operating voltage range			
	phase-phase	VAC	20...830
	phase-neutral	VAC	10...480
Voltage inputs operational frequency			
	min	Hz	45
	max	Hz	66
Voltage inputs measurement method			True RMS
Connection method			Single. two. three-phase with or without neutral. balanced three-phase systems
Current inputs			
Rated current (Ie)	A		5
Measurement range			0.01...6
Measurement method			TRMS
Overload capacity			+20% Ie through external CT with 5A secondary
Overload peak	A		50A for 1s
Primary current Ipn (/5)	A		60
Secondary output current	A		5
Overload withstand Ipn	%		120
Accuracy			
	VLN voltage		±0.5%
	VLL voltage		±0.5%

	Current			±0.5%
	Frequency			±0.05%
	Active power			±1%
Insulations				
Rated insulation voltage Ui IEC/EN		V		720
Rated impulse withstand voltage Uimp		kV		9.5
Operating frequency withstand voltage		kV		5.2
IEC rated short-time thermal current Ith		Ith for s		40...60
IEC rated dynamic current Idyn		Ith for s		2.5
Insulation dry type				Class E
Mechanical features				
Housing type				Polyamide
Terminals type				Fixed
Conductor cross section				
		min	mm²	0.2
		Max	mm²	4
		min	AWG	24
		Max	AWG	12
Tightening torque (Max)				
			Nm	0.8
			lbin	7
Fixing				Din rail
Weight			g	1035
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-20
		max	°C	+60
	Storage temperature			
		min	°C	-30
		max	°C	+80
Relative humidity			%	<90
Maximum Pollution degree				2
Protection degree				IP30
ETIM classification				
ETIM 8.0				EC002301 - Multifunction measuring instrument