

## FUSE FOR PHOTOVOLTAIC APPLICATIONS, FOR 10X85MM FUSES. 10KA BREAKING CAPACITY AT 1500VDC, 6A

|                                |     | 0   | The same of the sa |
|--------------------------------|-----|-----|--|
| Product designation            |     |     | Fuse 10x85mm   |
| Product type designation       |     |     | FE   |
| Operating voltage type         |     |     | DC   |
| Electrical features            |     |     |  |
| IEC maximum rated current (In) |     | Α   | 6  |
| IEC maximum rated voltage (Un) |     | V   | 1500   |
| Rated current (In)             |     | Α   | 6  |
| IEC fuse class                 |     |     | gPV  |
| Power consumption at 0,7 In    |     | W   | 1.1  |
| Power consumption at In        |     | W   | 2.7  |
| Preacring I2t                  |     | A2s | 68   |
| Total I2t at 1000Vdc           |     | A2s | 88   |
| Ambient conditions             |     |     |  |
| Operating temperature          |     |     |  |
|                                | min | °C  | -20  |
|                                | max | °C  | +70  |
| Storage temperature            |     |     |  |
|                                | min | °C  | -40  |
|                                | max | °C  | +80  |
| Max altitude                   |     | m   | 3000   |
| Mechanical features            |     |     |  |
| Weight                         |     | g   | 19   |
| Dimensions                     |     |     |  |





## Certifications and compliance

Compliance

IEC/EN/BS 60269-6

ETIM classification

**ETIM 8.0** 

EC002704 -Cylindrical fuse