



Contact characteristics

IEC Conventional free air thermal current $I_{th} \leq 40^{\circ}\text{C}$	A	500
Rated insulation voltage U_i IEC/EN	V	1000
Rated impulse withstand voltage U_{imp}	kV	12
Operating current I_e		
AC21A		
	400V	A 500
	500V	A 500
	690V	A 500
AC22A		
	400V	A 500
	500V	A 500
	690V	A 400
AC23A		
	400V	A 400
	500V	A 250
Power dissipation per pole max	W	28
Rated operational power AC23A		
	400V	kW 200
	690V	kW 173
Reactive power for control of capacitors at		
Rated short time current (1s) I_{cw} (rms)	kA	13
Conditional short-circuit current (rms)	kA	100
Short-circuit protection with fuse	Class/A	gG500
Making capacity AC23A 400V	A	6300
Mechanical life	cycles	10000
Electrical life AC21A	cycles	1000 (AC23A 400V)

Mechanical features

Operating position	normal allowable	Vertical plan Any
Fixing		Screw
Terminals	type screw	Bar M12
Tightening torque for terminals	max	Nm 24
	max	lbin 18
Conductor section		
Bar dimensions max		40x5

Ambient conditions

Operating temperature	min	$^{\circ}\text{C}$	-25
	max	$^{\circ}\text{C}$	55

Storage temperature

min	°C	-40
max	°C	70
	m	3000

Max altitude

Resistance & Protection


Frontal IP degree

IP20

Pollution degree

3


Dimensions



TYPE	A	B	C	D	ØE	F	G	H	J	K	L	M	N	O	P	Q	R Max	S	Ø T	U	V	Shaft extension	Terminal covers (N° of pcs/set)		
																						W	X (line 1)	Y (line 2)	Z (load)
GE0201 E GE0250 E GE0315 E GE0400 E	235 (9.25")	119.5 (4.70")	115.5 (4.55")	25 (0.98")	5.5 (0.22")	157 (6.18")	192 (7.56")	216 (8.50")	45 (1.77")	88 (3.46")	357 (14.05")	170 (6.69")	42 (1.65")	3 (0.12)	67 (2.64")	151 (5.94")	437 (17.2")	143 (5.63")	M10	133 (5.24")	142 (5.59")	GEX7227N GEX7375N GEX7536N □ 10 (0.6")	GEX82 12 (3)	GEX82 11 (3)	GEX83 12 (3)
GE0201 ET4 GE0250 ET4 GE0315 ET4 GE0400 ET4																							GEX82 13 (4)	GEX82 13 (4)	GEX83 12 (4)
GE0500 E GE0630 E GE0800 E																							GEX82 22 (3)	GEX82 21 (3)	GEX83 21 (3)
GE0500 ET4 GE0630 ET4 GE0800 ET4																							GEX82 23 (4)	GEX82 23 (4)	GEX83 22 (4)

Wiring diagrams

GE0201 ET4 - GE1600 ET4



Certifications and compliance

Compliance

IEC/EN 60947-1

IEC/EN 60947-3

Certifications

EAC

ETIM classification

ETIM 8.0

EC000216 -
Switch
disconnector