



Contact characteristics

IEC Conventional free air thermal current $I_{th} \leq 40^\circ\text{C}$	A	1000
Rated insulation voltage U_i IEC/EN	V	1000
Rated impulse withstand voltage U_{imp}	kV	12
Operating current I_e		
AC21A		
	400V	A 1000
	500V	A 1000
	690V	A 1000
AC22A		
	400V	A 1000
	500V	A 1000
	690V	A 630
AC23A		
	400V	A 1000
	500V	A 800
	690V	A 500
Power dissipation per pole max	W	50
Rated operational power AC23A		
	400V	kW 443
	690V	kW 478
Reactive power for control of capacitors at		
Rated short time current (1s) I_{cw} (rms)	kA	25
Conditional short-circuit current (rms)	kA	72
Short-circuit protection with fuse	Class/A	gG1000
Making capacity AC23A 400V	A	8000
Breaking capacity AC23A 400V	A	6400
Mechanical life	cycles	10000
Electrical life AC21A	cycles	500 (AC23A 400V)


Mechanical features

Operating position	normal allowable	Vertical plan Any
Fixing		Screw
Terminals	type screw	Bar M14
Tightening torque for terminals	max max	Nm 45 lbin 10
Conductor section		
Bar dimensions max		40x8

Ambient conditions


Operating temperature

	min	°C	-25
	max	°C	55
Storage temperature			
	min	°C	-40
	max	°C	70
Max altitude	m		3000
Resistance & Protection			
Frontal IP degree			IP20
Pollution degree			3
Dimensions			



Wiring diagrams

Four-pole disconnectors GE0160 T4 - GE1600 T4 GE0160 T4P



Certifications and compliance

Compliance	IEC/EN 60947-1
	IEC/EN 60947-3
Certifications	EAC

ETIM classification

ETIM 8.0	EC000216 - Switch disconnecter
----------	--------------------------------