



Contact characteristics

IEC Conventional free air thermal current $I_{th} \leq 40^{\circ}\text{C}$	A	1600
Rated insulation voltage U_i IEC/EN	V	1000
Rated impulse withstand voltage U_{imp}	kV	12
Operating current I_e		
AC21A		
	400V	A 1600
	500V	A 1600
	690V	A 1600
	1000V	A 1600
AC22A		
	400V	A 1600
	500V	A 1600
	690V	A 1600
AC23A		
	400V	A 1600
	500V	A 1600
	690V	A 1600
Power dissipation per pole max	W	63
Rated operational power AC23A		
	400V	kW 900
	690V	kW 1000
Reactive power for control of capacitors at		
Rated short time current (1s) I_{cw} (rms)	kA	50
Conditional short-circuit current (rms)	kA	100
Short-circuit protection with fuse	Class/A	gG/2x800
Making capacity AC23A 400V	A	16000
Breaking capacity AC23A 400V	A	12800
Mechanical life	cycles	3000

Mechanical features


Operating position	normal allowable	Vertical plan Any
Fixing		Screw
Terminals	type	M12
Tightening torque for terminals		
	min	Nm 50
	max	Nm 75
	min	Ibin 442
	max	Ibin 664
Conductor section		
Busbar IEC min	mm	2 busbars 50x10

Ambient conditions

Operating temperature

	min	°C	-25
	max	°C	+55
Storage temperature			
	min	°C	-40
	max	°C	+70
Max altitude		m	3000

Wiring diagrams



Certifications and compliance

Compliance	IEC/EN/BS 60947-1
	IEC/EN/BS 60947-3

ETIM classification

ETIM 8.0	EC000216 - Switch disconnecter
----------	--------------------------------