



Contact characteristics

IEC Conventional free air thermal current $I_{th} \leq 40^{\circ}\text{C}$	A	320
Rated insulation voltage U_i IEC/EN	V	1000
Rated impulse withstand voltage U_{imp}	kV	12
Operating current I_e		
AC-31B		
	400V	A 320
	500V	A 320
	690V	A 320
AC-32B		
	400V	A 320
	500V	A 320
	690V	A 320
AC-33B		
	400V	A 320
	500V	A 320
	690V	A 320
Power dissipation per pole max	W	20.8
Rated operational power AC23A		
	400V	kW 160
	690V	kW 315
Reactive power for control of capacitors at		
Rated short time current (1s) I_{cw} (rms)	kA	12.5
Rated short time current (0.3s) I_{cw} (rms)	kA	20
Conditional short-circuit current (rms)	kA	80
Short-circuit protection with fuse	Class/A	gG/355
Making capacity AC23A 400V	A	3200
Breaking capacity AC23A 400V	A	2560
Mechanical life	cycles	10000

Mechanical features

Operating position	normal allowable	Vertical plan Any
Fixing		Screw
Terminals	type	M10 x 25
Tightening torque for terminals		
	min	Nm 30
	max	Nm 37
	min	lbin 265
	max	lbin 327
Conductor section		
	IEC min	mm ² 1X182
	IEC max	mm ² 2X185
	AWG/kcmil min	1X400

AWG/kcmil max kcmil 2X350

Ambient conditions

Operating temperature

min	°C	-25
max	°C	+55



Storage temperature

min	°C	-40
max	°C	+70


Max altitude

m	3000
---	------

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

IEC/EN 60947-1
IEC/EN 60947-3
IEC/EN 60947-6-1

ETIM classification

ETIM 8.0

EC000216 -
Switch
disconnecter