



Contact characteristics

IEC Conventional free air thermal current $I_{th} \leq 40^{\circ}\text{C}$	A	1000
Rated insulation voltage U_i IEC/EN	V	1000
Rated impulse withstand voltage U_{imp}	kV	12
Operating current I_e		
AC21A		
	400V	A 1000
	500V	A 1000
	690V	A 1000
	1000V	A 1000
AC22A		
	400V	A 1000
	500V	A 1000
	690V	A 1000
AC23A		
	400V	A 1000
	500V	A 1000
	690V	A 1000
Power dissipation per pole max	W	63
Rated operational power AC23A		
	400V	kW 560
	690V	kW 1000
Reactive power for control of capacitors at		
Rated short time current (1s) I_{cw} (rms)	kA	50
Conditional short-circuit current (rms)	kA	100
Short-circuit protection with fuse	Class/A	gG/1000
Making capacity AC23A 400V	A	10000
Breaking capacity AC23A 400V	A	8000
Mechanical life	cycles	3000

Mechanical features

Operating position	normal allowable	Vertical plan Any
Fixing		Screw
Terminals	type	M12
Tightening torque for terminals		
	min	Nm 50
	max	Nm 75
	min	lbin 442
	max	lbin 664
Conductor section		
Busbar IEC min	mm	2 busbars 60x5

Ambient conditions

Operating temperature

		min	°C	-25
		max	°C	+55
Storage temperature				
		min	°C	-40
		max	°C	+70
Max altitude			m	3000
Certifications and compliance				
Compliance				
	IEC/EN/BS 60947-1			
	IEC/EN/BS 60947-3			
ETIM classification				
ETIM 8.0			EC002498 - Accessories/spare parts for low- voltage switch technology	