



Contact characteristics

IEC Conventional free air thermal current $I_{th} \leq 40^{\circ}\text{C}$	A	1200
Rated insulation voltage U_i IEC/EN	V	1000
Rated impulse withstand voltage U_{imp}	kV	12
Operating current I_e		
AC21A		
400V	A	1200
500V	A	1200
690V	A	1200
1000V	A	1200
AC22A		
400V	A	1200
500V	A	1200
690V	A	1200
AC23A		
400V	A	1200
500V	A	1200
690V	A	1200
Power dissipation per pole max	W	63
Rated operational power AC23A		
400V	kW	710
690V	kW	1000
Reactive power for control of capacitors at		
Rated short time current (1s) I_{cw} (rms)	kA	50
Conditional short-circuit current (rms)	kA	100
Short-circuit protection with fuse	Class/A	gG/1250
Making capacity AC23A 400V	A	12500
Breaking capacity AC23A 400V	A	10000
Mechanical life	cycles	3000

Mechanical features

Operating position	normal allowable	Vertical plan Any
Fixing		Screw
Terminals	type	M12
Tightening torque for terminals	min	Nm 50
	max	Nm 75
	min	lbin 442
	max	lbin 664

UL technical data

UL Standard		UL98
General purpose current rating	A	1200
Operating voltage max	V	600

Horsepower/FLA current three phase motor

240V	HP/A	200/480
480V	HP/A	500/590
600V	HP/A	500/472

Short circuit rating kA rms 100

Short circuit rating with fuse Class/A L/1200

UL Terminal kit lugs GLX510

Minimum enclosure dimensions at rated current

mm	mm	1220x610x305
----	----	--------------

Ambient conditions

Operating temperature


min	°C	-25
max	°C	+55

Storage temperature

min	°C	-40
max	°C	+70

Max altitude m 3000

Dimensions



Certifications and compliance

Compliance

IEC/EN/BS 60947-1

IEC/EN/BS 60947-3

Certifications

cULus

ETIM classification

ETIM 8.0

EC002498 -
Accessories/spare
parts for low-
voltage switch
technology